

Date:

# **QUINCKE'S METHOD**

### Aim

To determine the magnetic susceptibility of given solution by Quincke's method.

## **Apparatus required**

Electromagnet, power supply, U shaped glass tube, traveling microscope and Gauss

meter.

# Formula used

Susceptibility is given by  $\chi = 2g (\sigma - \rho) h/H_1^2 N/wb$ 

 $\sigma = (w_3 - w_2)/(w_2 - w_1)$ 

Where  $w_1$ - weight of empty tube (gm)

w<sub>2</sub> - weight of given liquid (gm)

w<sub>3</sub>- weight of water (gm)

# **Experimental Procedure**

The U-shaped tube consists of one narrow and one wide end which has to be filled (3/4) with the experimental liquid. The narrow end of the tube has to keep at the center of the magnetic field where strong magnetic field is developed by an electromagnet. It is fed by suitable dc power supply. The height of the liquid in the tube is viewed through a microscope. While switch ON the power supply the level of the liquid will change in the narrow limb. The difference in the height (with and without field) will give h. Repeat the experiment for different current value.

The magnetic field strength is measured with the help of Gauss meter. Place the Gauss probe vertically in between the electromagnet. By varying the current from 0 A to 4 A the magnetic field can be obtained.



KARPAGAM ACADEMY OF HIGHER EDUCATIONCLASS: I M.Sc., PhysicsCOURSE NAME: GENERAL PHYSICS PRACTICALS - IICOURSE CODE: 18PHP211Lab ManualBATCH-2018-2020







## Tabulation

Magnetic field strength

Current (A)	H <sub>1</sub> (oestered)
0.5	
1	
1.5	
2	
2.5	
3	
3.5	
4	

Current (A)	Height without field (h <sub>1</sub> ) cm	with field (h <sub>2</sub> ) cm	h= h <sub>1</sub> -h <sub>2</sub> cm	h/H <sub>1</sub> <sup>2</sup> x cm
0.5				

Prepared by Dr. B.Janarthanan (Assoc Prof) & Dr.S.Sharmila (Asst Prof) Department of Physics KAHE



CLASS: I M.Sc., Physics COURSE CODE: 18PHP211 COURSE NAME: GENERAL PHYSICS PRACTICALS - II Lab Manual BATCH-2018-2020

1		
1.5		
2		
2.5		
3		
3.5		
4		

# Observations

Density of the liquid =  $---- kg/m^3$ 

Acceleration due to gravity = -----  $m/s^2$ 

Weight of the empty tube = ----- gm

Weight of the tube with liquid = ------ gm

Weight of the tube with water = ------ gm

### Calculations

 $\sigma = (w_3 - w_2)/(w_2 - w_1)$ 

 $\chi = 2g (\sigma - \rho) h/(H_1^2) N/wb$ 

#### Result

The susceptibility of the given liquid is \_\_\_\_\_ by Quincke's method

#### Viva Voce

- 1. What is called susceptibility?
- 2. Define magnetic field?
- 3. Is this method applicable for all liquids?
- 4. What is the relation between susceptibility and permeability?



Date:

# **GOUY'S METHOD**

## Aim

To determine the magnetic susceptibility of a given liquid by a Gouy's method

# **Apparatus Required**

Gouy set up, experimental liquid, Gauss meter, Gouy tube, Electromagnet and power

supply.

# Formula Used

The magnetic susceptibility of the liquid is given by,  $\chi_m = \frac{2Mg}{A_0H_1^2} Nm^2/wb^2$ 

where, H<sub>1</sub> – magnetic field measured from gauss meter

 $\rho$  – density of the liquid (kg/m<sup>3</sup>)

A- Area of cross section of the Gouy tube (m)

- M- mass of the liquid (gm)
- g- acceleration due to gravity  $(m/s^2)$

# Theory

Gouy balance measures the apparent change in the mass of the sample as it is repelled or attracted by the region of high magnetic field between the poles.

# **Experimental Procedure**

The electromagnet is energized by a DC power supply. The variable magnetic field is provided by the wedge shaped pole pieces. The distance between the pole pieces can be adjusted with the help of handle provided on both sides of the pole pieces. A hook is provided at the bottom of the digital balance of Gouy set up; which can be used to suspend the Gouys tube. An experimental liquid is filled 3/4<sup>th</sup> of a tube and placed between the poles. Before switch ON the power supply, the digital balance must be zero and then hang the liquid on the hook. The mass of the liquid is noted from the digital balance.

Switch ON the power supply and vary the current from 0 to 4A in steps of 0.5 A and note the mass of the liquid in each case. The magnetic field strength is measured with the help of



Gauss meter. Place the Gauss probe vertically in between the electromagnet. By varying the current from 0 A to 4 A the magnetic field can be obtained.





COURSE NAME: GENERAL PHYSICS PRACTICALS - II Lab Manual BATCH-2018-2020

2.5			
3			
3.5			
4			

#### Observations

Acceleration due to gravity =  $----m/s^2$ 

**COURSE CODE: 18PHP211** 

Density of the liquid =  $---- kg/m^3$ 

Area of cross section of Gouy tube = ----- (m)

### Calculation

$$\chi_{\rm m} = \frac{2 {\rm Mg}}{{\rm A}\rho {\rm H}_1^2} \, {\rm Nm}^2 / {\rm wb}^2$$

#### Result

The susceptibility of the liquid by Gouy method is \_\_\_\_\_ Nm<sup>2</sup>/wb<sup>2</sup>

#### Note:

- 1. Reduce the current through the coil to zero slowly and then switch off the power supply.
- 2. Don't change the distance between the pole-pieces in between the experiment.
- 3. Switch off the digital balance after completing the experiment.

### Viva voce

- 1. What is called magnetic susceptibility?
- 2. Define magnetic field?
- 3. Is this method applicable for all liquids?s
- 4. What is the principle behind this method?



Date:

# **KELVIN'S DOUBLE BRIDGE**

### Aim

To determine the very low resistance and specific resistance by Kelvin's double bridge method.

# **Apparatus Required**

Kelvin's double bridge apparatus, ballistic galvanometer, copper wire.

# Formula used

The unknown resistance is given by  $y = R_3 \frac{R_2}{R_1} \Omega$ 

where, Rs-standard known resistance

Specific resistance is given by  $\rho = \frac{\pi r^2}{r} y$  ( $\Omega$ m)

Where, r- radius of the wire (m)

l- length of the wire (m)

# **Experimental Procedure**

To find the resistance of the specimen, the wire is stretched between plates; so that it makes a contact with the knife edges. The battery connected should be capable of providing a steady DC of 25 A. Galvanometer shoul be sensitive and provided with a universal shunt.

The standard resistance R3 and the ratio R2/R1 are set to give an appropriate value os unknown resistance. The galvanometer is shunted and the key is pressed to obtain the deflection. The value of R3 and slide wire resistance is given by equation  $y = R_3 \frac{R_2}{R_1}$ .

By knowing R3 and the ratio of R2/R1, the value of y can be calculated. R3 includes the resistance of lead as well as wire. In order to find the actual resistance either the resistance of load is subtracted from the observed value or a preliminary experiment is made to do away with the resistance of loads. This part is known as the setting of the zero of the bridge i.e the bridge is initially set at zero with respect to the resistance of the loads.







To find the load resistance

R2/R1 Ω	R3 Ω	R3(R2/R1) Ω

### Calculations

 $\rho = \frac{\pi r^2}{l} y (\Omega m)$ 

ρ=

Radius of the wire = -----

Length of the wire = -----

### Result

The unknown resistance is found to be = ------  $(\Omega)$ 

The specific resistance of a given wire is = ------

### Viva voce

- 1. What is the principle of Kelvin double bridge?
- 2. What is Wheatstone's bridge?
- 3. What is specific resistance?
- 4. Which galvanometer is used in this method?



Date:

# ULTRASONIC INTERFEROMETER

## Aim

To calculate the adiabatic compressibility of the given liquid.

# Apparatus

Ultrasonic interferometer, sample liquids, high frequency generator.

# Formula used

Compressibility, 
$$\beta = \frac{1}{\rho v^2}$$

where,  $v = \lambda x F$ 

$$\lambda = 2d/N$$

 $\rho$  – density of the liquid (kg/m<sup>3</sup>)

v- velocity of the liquid (m/s)

F- frequency of the wave (Hz)

d- total distance of micrometer (m)

# Theory

Ultrasonic interferometer is a simple device which yields accurate and consistent data, from which one can determine the velocity of ultrasonic sound in a liquid medium.

# **Experimental Procedure**

- Insert the quartz crystal in the socket at the base and clamp it tightly with the help of a screw provided on one side of the instrument.
- Unscrew the knurled cap of the cell and lift it away. Fill the middle portion with the experimental liquid and screw the knurled cap tightly.
- Then connect the high frequency generator with the cell.
- There are two knobs on the instrument- "Adj" and "Gain". With "Adj", the position of the needle on the ammeter is adjusted. The knob "Gain" is used to increase the sensitivity of the instrument.



- Increase the micrometer setting till the anode current in the ammeter shows a maximum.
- Note down the micrometer reading.
- Continue to increase the micrometer setting, noting the reading at each maximum. Count any number of maxima and call it as *n*. Subtract the reading at the first maximum from the reading at the last maximum.
- Then calculate the velocity of the wave through the medium.
- Knowing the density of the medium, the adiabatic compressibility can be calculated using the equation.



Fig.1

Deflection	Micrometer reading	D	Wavelength (Å)
	(m)		

Calculation

Result

The velocity of the liquid = ----m/s

Compressibility of liquid = -----  $N/m^2$ 



Date:

# LASER DIFFRACTION USING A RULER

### Aim

To determine the wavelength of the light using He-Ne laser and scale.

# **Apparatus Required**

He-Ne laser, white screen, meter scale, engraved foot scale.

# Formula used

$$\lambda = \frac{\mathrm{d}}{\mathrm{2}\mathrm{D}^2} \left(\frac{\mathrm{y}_\mathrm{m}^2 - \mathrm{y}_\mathrm{0}^2}{\mathrm{m}}\right) \mathrm{\AA}$$

where,  $\lambda$ - wavelength of the laser Å

m-order

d- distance between the engraved screen and the laser beam (m)

# **Experimental Procedure**

- (i) Laser is placed on a magnetic mount to make a small angle with the ruler.
- (ii) Measure the distance (d) between the ruler and the screen.
- (iii) By adjusting the position of the ruler, the laser beam is focused on the engraved scale.
- (iv) Various spot is viewed on the screen and noted as y0, y1, .....

(v) The ruler is removed and the position of the direct beam is alos noted and the distance is measure.









## Calculation

$$\lambda = \frac{d}{2D^2} \left( \frac{y_m^2 - y_0^2}{m} \right) \mathring{A}$$

### Result

The wavelength of the light using He-Ne laser is tabulated.

### Viva voce

- 1. What is LASER?
- 2. What is the wavelength of He-Ne laser?
- 3. What is called diffraction?
- 4. How the fringes are formed?



Date:

# HALL EFFECT

## Aim

To study the Hall Effect and to determine the hall coefficient and number of charge carrier per unit volume.

# **Apparatus Required**

Hall Effect kit, Gauss meter and electromagnet.

# Formula Used

Hall coefficient is given by,  $R_H = (V_H/I_C)(t/B)$  ohm<sup>2</sup>Wmb

where,  $V_H$  – Hall voltage (V)

B – magnetic field

t- thickness of the specimen (m)

Ic – current (mA)

Number of charge carriers per unit volume,  $n = \frac{1}{R_{H}}$ 

e- charge of an electron

Hall angle,  $\tan \theta_H = \mu_H B$ 

A- Magnetic field

Hall Mobility,  $\mu_{\rm H} = \frac{R_{\rm H}}{\rho}$ 

 $\rho$  –density of the material (kg/m³)

# **Experimental Procedure**

(i) Place the specimen in the magnetic field.

(ii) With the help of rheostat allow the current to the semiconductor and measure the hall voltage  $(V_H)$  and Hall current Vx.



- (iii) Increase the current (Ix) and measure Vx and V<sub>H</sub>. Plot a graph between  $V_H$  and Ix.
- (iv) Using the Gauss meter, measure the magnetic field.

Dimmer state	Hall probe current	Hall probe voltage
current (A)	(mA)	(mV)
0.5	1.0	
	2.0	
	3.0	
1	1.0	
	2.0	
	3.0	
1.5	1.0	
	2.0	
	3.0	

[	Dimmer state	Hall probe current	Hall probe voltage
	current (A)	(mA)	(mV)
Ī	0.5		
	1.0		
	1.5	1.0	
	2.0		
	2.5		
Ī	0.5		
	1.0	2.0	
	1.5		
	2.0		
	2.5		
Ī	0.5		
	1.0		
	1.5	3.0	
	2.0		
	2.5		



current (A)	Magnetic field (B)
0.5	
1.0	
1.5	
2.0	
2.5	
3.0	
3.5	

### Calculation

#### Result

Hall coefficient = ------No. of charge carriers, = ------Hall angle = ------Mobility = ------

### Viva Voce

- 1. What is called Hall effect?
- 2. What is called mobility?
- 3. What is called Hall coefficient?