

**KARPAGAM ACADEMY OF HIGHER EDUCATION**

(Deemed University)

(Established Under Section 3 of UGC Act 1956)

Coimbatore - 641021.

(For the candidates admitted from 2015 onwards)

**DEPARTMENT OF COMPUTER SCIENCE, CA & IT****SUBJECT : HTML PROGRAMMING****SEMESTER : IV****SUBJECT CODE : 17CSU404A****CLASS : II B.Sc.CS****Course Outcome**

This course design focuses on the structure of the website including the information architecture, the layout or the pages and the conceptual design with branding. HTML helps the students for developing dynamic web pages.

**Learning Outcome**

- Understand the fundamentals of HTML and use different formatting options
- creation of tables and frames
- Relate with DHTML and CSS
- To work with open source applications that deal with database and website development.

**Unit-I:****Introduction the Basics:** The Head, the Body, Colors, Attributes, Lists, ordered and unordered**Unit-II****Links Introduction:** Relative Links, Absolute Links, Link Attributes, Using the ID Attribute to Link within a Document**Unit-III:****Images: Putting** an Image on a Page, Using Images as Links, Putting an Image in the Background**Unit IV:****Tables: Creating** a Table, Table Headers, Captions, Spanning Multiple Columns, Styling Table

**Unit V :**

**Forms: Basic** Input and Attributes, Other Kinds of Inputs, Styling forms with CSS, Where to Go from Here.

**Suggested Readings:**

1. Steven Holzner, "*HTML Black Book*", Dreamtech Press, New Delhi, 2009.
2. Virginia DeBolt, "*Integrated HTML and CSS A Smarter, Faster Way to Learn*", Wiley / Sybex, 2006.
3. Cassidy Williams, Camryn Williams, "*Introduction to HTML and CSS*", O'Reilly, 2015.
4. Ramesh Bangia, "*Web Technology*", Firewall Media, New Delhi, 2010.

**WEBSITES**

1. [www.w3schools.com/](http://www.w3schools.com/)
2. [alexle.net/archives/category/web-technology](http://alexle.net/archives/category/web-technology)
3. [www.tutorialspoint.com/html/html\\_tutorial.pdf](http://www.tutorialspoint.com/html/html_tutorial.pdf)
4. [en.wikipedia.org/wiki/Php](http://en.wikipedia.org/wiki/Php)
5. [Www.W3schools.Com/Php/Default. Asp](http://Www.W3schools.Com/Php/Default.Asp)



# KARPAGAM ACADEMY OF HIGHER EDUCATION

(Deemed University)

(Established Under Section 3 of UGC Act 1956)

Coimbatore - 641021.

(For the candidates admitted from 2016 onwards)

## DEPARTMENT OF COMPUTER SCIENCE, CA & IT

**SUBJECT : HTML PROGRAMMING**

**SEMESTER : IV**

**L T P C**

**SUBJECT CODE: 17CSU404A**

**CLASS : II B.Sc.CS**

**3 0 0 3**

### LECTURE PLAN

**STAFF NAME: Dr.P.TAMIL SELVAN**

S.No	Lecture Duration (Hr)	Topics	Support Materials
<b>UNIT-I</b>			
1.	1	• <b>Introduction to HTML</b>	S1:7-10
2.	1	• The Head	S1:23-25
3.	1	• The Body	S1:30-46
4.	1	• Colors, Attributes	S1:188,W2
5.	1	• Lists, Ordered , Unordered	S1:276-285
6.	1	• Recapitulation and Discussion of important questions	
		<b>Total No of Hours Planned For Unit – I</b>	<b>6</b>
<b>UNIT-II</b>			
1.	1	• <b>Links Introduction</b> , Relative Links, Absolute Links	S4:91, S1:251-254 W1
2.	1	• Use styling links in your web page. • Link Attributes	S1:255, S1:256
3.	1	• Using the ID Attribute to Link Within a Document	S1:258
4.	1	• The <a> Element's and Other Attributes • The accesskey Attribute	S1:261

5.	1	<ul style="list-style-type: none"> <li>• The href lang Attribute</li> <li>• The rel Attribute</li> </ul>	S1:244, W2
6.	1	<ul style="list-style-type: none"> <li>• Recapitulation and Discussion of important questions</li> </ul>	
		<b>Total No of Hours Planned For Unit – II</b>	<b>6</b>
<b>UNIT-III</b>			
1.	1	<ul style="list-style-type: none"> <li>• Putting an Image on a Page</li> </ul>	S4:118
2.	1	<ul style="list-style-type: none"> <li>• Adding images Using the &lt;img&gt; element               <ul style="list-style-type: none"> <li>➤The src Attribute , The alt Attribute</li> </ul> </li> </ul>	S1:202-204
3.	1	<ul style="list-style-type: none"> <li>• The height and width Attributes</li> </ul>	S1:206
4.	1	<ul style="list-style-type: none"> <li>• Putting an Image in the Background</li> </ul>	S1:214
5.	1	<ul style="list-style-type: none"> <li>• Styling Images, Adding Images to a Web Page</li> </ul>	S4:119,W2 S1:196
6.	1	<ul style="list-style-type: none"> <li>• Recapitulation and Discussion of important questions</li> </ul>	
		<b>Total No of Hours Planned For Unit – III</b>	<b>6</b>
<b>UNIT-IV</b>			
1.	1	<ul style="list-style-type: none"> <li>• Creating a Table , Table Headers, Captions</li> </ul>	S1:298-303 S1:334-335
2.	1	<ul style="list-style-type: none"> <li>• Spanning Multiple Columns</li> <li>• Spanning Multiple rows</li> </ul>	S1:309
3.	1	<ul style="list-style-type: none"> <li>• Styling Table</li> </ul>	S1:311
4.	1	<ul style="list-style-type: none"> <li>• The dir Attribute</li> <li>• The &lt;tr&gt; Element Contains Table Rows</li> </ul>	S1:327-328
5.	1	<ul style="list-style-type: none"> <li>• The &lt;td&gt; and &lt;th&gt; Elements Represent Table Cells</li> </ul>	S1:329-331, W1
6.	1	<ul style="list-style-type: none"> <li>• Recapitulation and Discussion of important questions</li> </ul>	
		<b>Total No of Hours Planned For Unit – IV</b>	<b>6</b>
<b>UNIT-V</b>			
1.	1	<ul style="list-style-type: none"> <li>• Forms , Basic Input and Attributes,</li> </ul>	S4:136-139
2.	1	<ul style="list-style-type: none"> <li>• Other Kinds of Inputs</li> </ul>	S4:145
3.	1	<ul style="list-style-type: none"> <li>• Styling forms with CSS</li> <li>• Where To Go From Here</li> </ul>	S4:207

4.	1	• Recapitulation and Discussion of important questions	
5.	1	<b>Discussion of previous ESE Question papers</b>	
6.	1	<b>Discussion of previous ESE Question papers</b>	
		<b>Total No of Hours Planned For Unit – V</b>	<b>6</b>
		<b>Total No. of Hours Planned: 30</b>	

**Suggested Readings:**

1. Steven Holzner, "*HTML Black Book*", Dreamtech Press, New Delhi, 2009.
2. Virginia DeBolt, "*Integrated HTML and CSS A Smarter, Faster Way to Learn*", Wiley / Sybex, 2006.
3. Cassidy Williams, Camryn Williams, "*Introduction to HTML and CSS*", O'Reilly, 2015.
4. Ramesh Bangia, "*Web Technology*", Firewall Media, New Delhi, 2010.

**WEBSITES**

1. [www.w3schools.com/](http://www.w3schools.com/)
2. [alexle.net/archives/category/web-technology](http://alexle.net/archives/category/web-technology)
3. [jmarshall.com/easy/](http://jmarshall.com/easy/)
4. [www.php.net/](http://www.php.net/)
5. [en.wikipedia.org/wiki/Php](http://en.wikipedia.org/wiki/Php)
6. [Www.W3schools.Com/Php/Default. Asp](http://Www.W3schools.Com/Php/Default.Asp)



**UNIT-I**  
**SYLLABUS**

**HTML : Introduction The Basics:** The Head, the Body, Colors, Attributes, Lists, ordered and unordered

What is an html File?

HTML stands for Hypertext Markup Language, and it is the most widely used language to write Web Pages.

- Hypertext refers to the way in which Web pages (HTML documents) are linked together. Thus, the link available on a webpage is called Hypertext.
- As its name suggests, HTML is a Markup Language which means you use HTML to simply "mark-up" a text document with tags that tell a Web browser how to structure it to display.

Originally, HTML was developed with the intent of defining the structure of documents like headings, paragraphs, lists, and so forth to facilitate the sharing of scientific information between researchers.

Now, HTML is being widely used to format web pages with the help of different tags available in HTML language.

**Basic HTML Document**

In its simplest form, following is an example of an HTML document:

```
<!DOCTYPE html>
<html>
<head>
<title>This is document title</title>
</head>
<body>
```



```
<h1>This is a heading</h1>
```

```
<p>Document content goes here.....</p>
```

```
</body>
```

```
</html>
```

## HTML Tags

As told earlier, HTML is a markup language and makes use of various tags to format the content. These tags are enclosed within angle braces **<Tag Name>**. Except few tags, most of the tags have their corresponding closing tags. For example, **<html>** has its closing tag **</html>** and **<body>** tag has its closing tag **</body>** tag etc.

Above example of HTML document uses the following tags:

Tag	Description
<!DOCTYPE...>	This tag defines the document type and HTML version.
<html>	This tag encloses the complete HTML document and mainly comprises of document header which is represented by <head>...</head> and document body which is represented by <body>...</body> tags.
<head>	This tag represents the document's header which can keep other HTML tags like <title>, <link> etc.
<title>	The <title> tag is used inside the <head> tag to mention the document title.
<body>	This tag represents the document's body which keeps other HTML tags like <h1>, <div>, <p> etc.
<h1>	This tag represents the heading.
<p>	This tag represents a paragraph.



## HTML Document Structure

A typical HTML document will have the following structure:

Document declaration tag

```
<html>
```

```
<head>
```

Document header related tags

```
</head>
```

```
<body>
```

Document body related tags

```
</body>
```

```
</html>
```

We will study all the header and body tags in subsequent chapters, but for now let's see what is document declaration tag.

### The<!DOCTYPE> Declaration

The <!DOCTYPE> declaration tag is used by the web browser to understand the version of the HTML used in the document. Current version of HTML is 5 and it makes use of the following declaration:

```
<!DOCTYPE html>
```

There are many other declaration types which can be used in HTML document depending on what version of HTML is being used. We will see more details on this while discussing

<!DOCTYPE...> tag along with other HTML tags.





## HTML Basic Tags

### Heading Tags

Any document starts with a heading. You can use different sizes for your headings. HTML also has six levels of headings, which use the elements **<h1>**, **<h2>**, **<h3>**, **<h4>**, **<h5>**, and **<h6>**. While displaying any heading, browser adds one line before and one line after that heading.

### Example

```
<!DOCTYPE html>
<html>
<head>
<title>Heading Example</title>
</head>
<body>
<h1>This is heading 1</h1>
<h2>This is heading 2</h2>
<h3>This is heading 3</h3>
<h4>This is heading 4</h4>
<h5>This is heading 5</h5>
<h6>This is heading 6</h6>
</body>
</html>
```

### Paragraph Tag

The **<p>** tag offers a way to structure your text into different paragraphs. Each paragraph of text should go in between an opening **<p>** and a closing **</p>** tag as shown below in the example:

### Example

```
<!DOCTYPE html>
<html>
```



```
<head>
```

```
<title>Paragraph Example</title>
```

```
</head>
```

```
<body>
```

```
<p>Here is a first paragraph of text.</p>
```

```
<p>Here is a second paragraph of text.</p>
```

```
<p>Here is a third paragraph of text.</p>
```

```
</body>
```

```
</html>
```

### Line Break Tag

Whenever you use the **<br />** element, anything following it starts from the next line. This tag is an example of an **empty** element, where you do not need opening and closing tags, as there is nothing to go in between them.

The **<br />** tag has a space between the characters **br** and the forward slash. If you omit this space, older browsers will have trouble rendering the line break, while if you miss the forward slash character and just use **<br>** it is not valid in XHTML.

### Example

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>Line Break Example</title>
```

```
</head>
```

```
<body>
```

```
<p>Hello<br />
```

```
You delivered your assignment on time.<br />
```

```
Thanks<br />
```

```
Mahnaz</p>
```

```
</body>
```



&lt;/html&gt;

## Horizontal Lines

Horizontal lines are used to visually break-up sections of a document. The **<hr>** tag creates a line from the current position in the document to the right margin and breaks the line accordingly.

For example, you may want to give a line between two paragraphs as in the given example below:

### Example

```
<!DOCTYPE html>
<html>
<head>
<title>Horizontal Line Example</title>
</head>
<body>
<p>This is paragraph one and should be on top</p>
<hr />
<p>This is paragraph two and should be at bottom</p>
</body>
</html>
```

Again **<hr />** tag is an example of the empty element, where you do not need opening and closing tags, as there is nothing to go in between them.

The **<hr />** element has a space between the characters **hr** and the forward slash. If you omit this space, older browsers will have trouble rendering the horizontal line, while if you miss the forward slash character and just use **<hr>** it is not valid in XHTML.

## Preserve Formatting

Sometimes, you want your text to follow the exact format of how it is written in the HTML document. In these cases, you can use the preformatted tag **<pre>**.

Any text between the opening **<pre>** tag and the closing **</pre>** tag will preserve the formatting of the source document.



### Example

```
<!DOCTYPE html>

<html>

<head>

<title>Preserve Formatting Example</title>

</head>

<body>

<pre>
function testFunction( strText ){
alert (strText)
}
</pre>
</body>
</html>
```

This will produce the following result:

```
function testFunction( strText ){
alert (strText)
}
```

Try using the same code without keeping it inside **<pre>...</pre>** tags

### HTML element

An **HTML element** is defined by a starting tag. If the element contains other content, it ends with a closing tag, where the element name is preceded by a forward slash as shown below with few tags:

Start Tag	Content	End Tag
<p>	This is paragraph content.	</p>
<h1>	This is heading content.	</h1>
<div>	This is division content.	</div>



So here `<p>....</p>` is an HTML element, `<h1>...</h1>` is another HTML element. There are some HTML elements which don't need to be closed, such as `<img.../>`, `<hr />` and `<br />` elements. These are known as **void elements**.

HTML documents consists of a tree of these elements and they specify how HTML documents should be built, and what kind of content should be placed in what part of an HTML document.

### HTML Tag vs. Element

An HTML element is defined by a starting tag. If the element contains other content, it ends with a closing tag.

For example, `<p>` is starting tag of a paragraph and `</p>` is closing tag of the same paragraph but `<p>This is paragraph</p>` is a paragraph element.

### HTML – COLORS

Colors are very important to give a good look and feel to your website. You can specify colors on page level using `<body>` tag or you can set colors for individual tags using **bgcolor** attribute.

The `<body>` tag has following attributes which can be used to set different colors:

- ☐ **bgcolor** - sets a color for the background of the page.
- ☐ **text** - sets a color for the body text.
- ☐ **alink** - sets a color for active links or selected links.
- ☐ **link** - sets a color for linked text.
- ☐ **vlink** - sets a color for visited links - that is, for linked text that you have already clicked on.

### HTML Color Coding Methods

There are following three different methods to set colors in your web page:

- ☐ **Color names** - You can specify color names directly like green, blue or red.
- ☐ **Hex codes** - A six-digit code representing the amount of red, green, and blue that makes up the color.
- ☐ **Color decimal or percentage values** - This value is specified using the `rgb()` property.

Now we will see these coloring schemes one by one.



## HTML Colors - Color Names

You can specify direct a color name to set text or background color. W3C has listed 16 basic color names that will validate with an HTML validator but there are over 200 different color names supported by major browsers.

### HTML Standard 16 Colors

Here is the list of W3C Standard 16 Colors names and it is recommended to use them.

Black	Gray	Silver	White
Yellow	Lime	Aqua	Fuchsia
Red	Green	Blue	Purple
Maroon	Olive	Navy	Teal

### Example

Here are the examples to set background of an HTML tag by color name:

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Colors by Name</title>
</head>
<body text="blue" bgcolor="green">
<p>Use different color names for for body and table and see the result.</p>
<table bgcolor="black">
<tr>
<td>
<font color="white">This text will appear white on black background.</font>
</td>
</tr>
</table>
</body>
</html>
```



### **HTML Colors - Hex Codes**

A hexadecimal is a 6 digit representation of a color. The first two digits(RR) represent a red value, the next two are a green value(GG), and the last are the blue value(BB).

A hexadecimal value can be taken from any graphics software like Adobe Photoshop, Paintshop Pro or MS Paint.

Each hexadecimal code will be preceded by a pound or hash sign #. Following is a list of few colors using hexadecimal notation.

#### **Color HEX**

#000000

#FF0000

#00FF00

#0000FF

#FFFF00

#00FFFF

#FF00FF

#C0C0C0

#FFFFFF

### **HTML Colors - RGB Values**

This color value is specified using the **rgb( )** property. This property takes three values, one each for red, green, and blue. The value can be an integer between 0 and 255 or a percentage.

**Note:** All the browsers does not support rgb() property of color so it is recommended not to use it.

Following is a list to show few colors using RGB values.

#### **Color RGB**

rgb(0,0,0)

rgb(255,0,0)

rgb(0,255,0)

rgb(0,0,255)



rgb(255,255,0)

rgb(0,255,255)

rgb(255,0,255)

rgb(192,192,192)

rgb(255,255,255)

### Example

Here are the examples to set background of an HTML tag by color code using rgb() values:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>HTML Colors by RGB code</title>
```

```
</head>
```

```
<body text="rgb(0,0,255)" bgcolor="rgb(0,255,0)">
```

```
<p>Use different color code for for body and table and see the result.</p>
```

```
<table bgcolor="rgb(0,0,0)">
```

```
<tr>
```

```
<td>
```

```
<font color="rgb(255,255,255)">This text will appear white on black background.</font>
```

```
</td>
```

```
</tr>
```

```
</table>
```

```
</body>
```

```
</html>
```





## HTML – ATTRIBUTES

We have seen few HTML tags and their usage like heading tags **<h1>**, **<h2>**, paragraph tag **<p>** and other tags. We used them so far in their simplest form, but most of the HTML tags can also have attributes, which are extra bits of information.

An attribute is used to define the characteristics of an HTML element and is placed inside the element's opening tag. All attributes are made up of two parts: a **name** and a **value**:

- The **name** is the property you want to set. For example, the paragraph **<p>** element in the example carries an attribute whose name is **align**, which you can use to indicate the alignment of paragraph on the page.
- The **value** is what you want the value of the property to be set and always put within quotations. The below example shows three possible values of align attribute: **left**, **center** and **right**.

Attribute names and attribute values are case-insensitive. However, the World Wide Web Consortium (W3C) recommends lowercase attributes/attribute values in their HTML 4 recommendation.

### Example

```
<!DOCTYPE html>
<html>
<head>
<title>Align Attribute Example</title>
</head>
<body>
<p align="left">This is left aligned</p>
<p align="center">This is center aligned</p>
<p align="right">This is right aligned</p>
</body>
</html>
```



This will display the following result:

This is left aligned

### Core Attributes

The four core attributes that can be used on the majority of HTML elements (although not all) are:

- ☐ Id
- ☐ Title
- ☐ Class
- ☐ Style

### The Id Attribute

The **id** attribute of an HTML tag can be used to uniquely identify any element within an HTML page. There are two primary reasons that you might want to use an id attribute on an element:

- ☐ If an element carries an id attribute as a unique identifier, it is possible to identify just that element and its content.
- ☐ If you have two elements of the same name within a Web page (or style sheet), you can use the id attribute to distinguish between elements that have the same name.

We will discuss style sheet in separate tutorial. For now, let's use the id attribute to distinguish between two paragraph elements as shown below.

### Example

```
<p id="html">This para explains what is HTML</p>
```

```
<p id="css">This para explains what is Cascading Style Sheet</p>
```

### The title Attribute

The **title** attribute gives a suggested title for the element. The syntax for the **title** attribute is similar as explained for **id** attribute:

The behavior of this attribute will depend upon the element that carries it, although it is often displayed as a tooltip when cursor comes over the element or while the element is loading.

### Example

```
<!DOCTYPE html>
```



```
<html>
```

```
<head>
```

```
<title>The title Attribute Example</title>
```

```
</head>
```

```
<body>
```

```
<h3 title="Hello HTML!">Titled Heading Tag Example</h3>
```

```
</body>
```

```
</html>
```

This will produce the following result:

### **Titled Heading Tag Example**

Now try to bring your cursor over "Titled Heading Tag Example" and you will see that whatever title you used in your code is coming out as a tooltip of the cursor.

### **The class Attribute**

The **class** attribute is used to associate an element with a style sheet, and specifies the class of element. You will learn more about the use of the class attribute when you will learn Cascading Style Sheet (CSS). So for now you can avoid it.

The value of the attribute may also be a space-separated list of class names. For example:

```
class="className1 className2 className3"
```

### **The style Attribute**

The style attribute allows you to specify Cascading Style Sheet (CSS) rules within the element.

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>The style Attribute</title>
```

```
</head>
```

```
<body>
```

```
<p style="font-family:arial; color:#FF0000;">Some text...</p>
```

```
</body>
```

```
</html>
```

This will produce the following result:



Some text...

At this point of time, we are not learning CSS, so just let's proceed without bothering much about CSS. Here, you need to understand what are HTML attributes and how they can be used while formatting content.

### **Internationalization Attributes**

There are three internationalization attributes, which are available for most (although not all) XHTML elements.

- dir

- ☐ lang

- ☐ xml:lang

### **The dir Attribute**

The **dir** attribute allows you to indicate to the browser about the direction in which the text should flow. The dir attribute can take one of two values, as you can see in the table that follows:

<b>Value</b>	<b>Meaning</b>
ltr	Left to right (the default value)
rtl	Right to left (for languages such as Hebrew or Arabic that are read right to left)

### **Example**

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
<title>English Language Page</title>
```

```
</head>
```

```
<body>
```

This page is using English Language

```
</body>
```



&lt;/html&gt;

### The xml:lang Attribute

The *xml:lang* attribute is the XHTML replacement for the *lang* attribute. The value of the *xml:lang* attribute should be an ISO-639 country code as mentioned in previous section.

### Generic Attributes

Here's a table of some other attributes that are readily usable with many of the HTML tags.

Attribute	Options	Function
align	right, left, center	Horizontally aligns tags
valign	top, middle, bottom	Vertically aligns tags within an HTML element.
bgcolor	numeric, hexadecimal, RGB values	Places a background color behind an element
background	URL	Places a background image behind an element
id	User Defined	Names an element for use with Cascading Style Sheets.
class	User Defined	Classifies an element for use with Cascading Style Sheets.

## HTML – LISTS

HTML offers web authors three ways for specifying lists of information. All lists must contain one or more list elements. Lists may contain:

- ☐ **<ul>** - An unordered list. This will list items using plain bullets.
- ☐ **<ol>** - An ordered list. This will use different schemes of numbers to list your items.
- ☐ **<dl>** - A definition list. This arranges your items in the same way as they are arranged in a dictionary.



## HTML Unordered Lists

An unordered list is a collection of related items that have no special order or sequence. This list is created by using HTML **<ul>** tag. Each item in the list is marked with a bullet.

### Example

```
<!DOCTYPE html>

<html>

<head>

<title>HTML Unordered List</title>

</head>

<body>

<ul>

<li>Beetroot</li>

<li>Ginger</li>

<li>Potato</li>

<li>Radish</li>

</ul>

</body>

</html>
```

This will produce the following result:

- ☐ Beetroot
- ☐ Ginger
- ☐ Potato
- ☐ Radish

### The type Attribute

You can use **type** attribute for **<ul>** tag to specify the type of bullet you like. By default, it is a disc. Following are the possible options:

```
<ul type="square">

<ul type="disc">

<ul type="circle">
```

### Example



Following is an example where we used `<ul type="square">`

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Unordered List</title>
</head>
<body>
<ul type="square">
<li>Beetroot</li>
<li>Ginger</li>
<li>Potato</li>
<li>Radish</li>
</ul>
</body>
</html>
```

This will produce the following result:

- ☐ Beetroot
- ☐ Ginger
- ☐ Potato
- ☐ Radish

### Example

Following is an example where we used `<ul type="disc">`:

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Unordered List</title>
</head>
<body>
<ul type="disc">
```



```
<li>Beetroot</li>
```

```
<li>Ginger</li>
```

```
<li>Potato</li>
```

```
<li>Radish</li>
```

```
</ul>
```

```
</body>
```

```
</html>
```

This will produce the following result:

☐ Beetroot

☐ Ginger

☐ Potato

☐ Radish

### Example

Following is an example where we used `<ul type="circle">`:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>HTML Unordered List</title>
```

```
</head>
```

```
<body>
```

```
<ul type="circle">
```

```
<li>Beetroot</li>
```

```
<li>Ginger</li>
```

```
<li>Potato</li>
```

```
<li>Radish</li>
```

```
</ul>
```

```
</body>
```

```
</html>
```

This will produce the following result:

o Beetroot





- o Ginger

- o Potato

- o Radish

### HTML Ordered Lists

If you are required to put your items in a numbered list instead of bulleted, then HTML ordered list will be used. This list is created by using **<ol>** tag. The numbering starts at one and is incremented by one for each successive ordered list element tagged with **<li>**.

#### Example

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Ordered List</title>
</head>
<body>
<ol>
<li>Beetroot</li>
<li>Ginger</li>
<li>Potato</li>
<li>Radish</li>
</ol>
</body>
</html>
```

This will produce the following result:

1. Beetroot
2. Ginger
3. Potato
4. Radish

#### The type Attribute



You can use **type** attribute for <ol> tag to specify the type of numbering you like. By default, it is a number. Following are the possible options:

<ol type="1"> - Default-Case Numerals.

<ol type="I"> - Upper-Case Numerals.

<ol type="i"> - Lower-Case Numerals.

<ol type="a"> - Lower-Case Letters.

<ol type="A"> - Upper-Case Letters.

### **Example**

Following is an example where we used <ol type="1">

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Ordered List</title>
</head>
<body>
<ol type="1">
<li>Beetroot</li>
<li>Ginger</li>
<li>Potato</li>
<li>Radish</li>
</ol>
</body>
</html>
```

This will produce the following result:

1. Beetroot
2. Ginger
3. Potato
4. Radish

### **Example**

Following is an example where we used <ol type="I">



<!DOCTYPE html>

<html>

<head>

<title>HTML Ordered List</title>

</head>

<body>

<ol type="I">

<li>Beetroot</li>

<li>Ginger</li>

<li>Potato</li>

<li>Radish</li>

</ol>

</body>

</html>

This will produce the following result:

I. Beetroot

II. Ginger

III. Potato

IV. Radish

### Example

Following is an example where we used <ol type="i">

<!DOCTYPE html>

<html>

<head>

<title>HTML Ordered List</title>

</head>

<body>

<ol type="i">

<li>Beetroot</li>

<li>Ginger</li>



```
<li>Potato</li>
```

```
<li>Radish</li>
```

```
</ol>
```

```
</body>
```

```
</html>
```

This will produce the following result:

i. Beetroot

ii. Ginger

iii. Potato

iv. Radish

### Example

Following is an example where we used `<ol type="A">`

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>HTML Ordered List</title>
```

```
</head>
```

```
<body>
```

```
<ol type="A">
```

```
<li>Beetroot</li>
```

```
<li>Ginger</li>
```

```
<li>Potato</li>
```

```
<li>Radish</li>
```

```
</ol>
```

```
</body>
```

```
</html>
```

This will produce the following result:

A. Beetroot

B. Ginger

C. Potato



## D. Radish

### Example

Following is an example where we used <ol type="a">

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Ordered List</title>
</head>
<body>
<ol type="a">
<li>Beetroot</li>
<li>Ginger</li>
<li>Potato</li>
<li>Radish</li>
</ol>
</body>
</html>
```

This will produce the following result:

- a. Beetroot
- b. Ginger
- c. Potato
- d. Radish

### HTML Definition Lists

HTML and XHTML supports a list style which is called **definition lists** where entries are listed like in a dictionary or encyclopedia. The definition list is the ideal way to present a glossary, list of terms, or other name/value list.

Definition List makes use of following three tags.

- ☐ <dl> - Defines the start of the list
- ☐ <dt> - A term
- ☐ <dd> - Term definition



☐ </dl> - Defines the end of the list

### Example

```
<!DOCTYPE html>

<html>

<head>

<title>HTML Definition List</title>

</head>

<body>

<dl>

<dt><b>HTML</b></dt>

<dd>This stands for Hyper Text Markup Language</dd>

<dt><b>HTTP</b></dt>

<dd>This stands for Hyper Text Transfer Protocol</dd>

</dl>

</body>

</html>
```

This will produce the following result:

### HTML

This stands for Hyper Text Markup Language

### HTTP

This stands for Hyper Text Transfer Protocol



### **Possible Questions**

#### **Unit-1**

##### **Part – A**

(1 Mark)

(Online Questions)

##### **Part – B**

(Two Marks)

1. What is html?
2. Define metadata.
3. Define Attribute in html.
4. How preserve formatting tag is used in Html.
5. List out the different types of lists in Html.
6. List out Ordered List.
7. What is meant by paragraph tag?
8. List out definition List.
9. What are the three color methods?
10. List out Unordered List.
11. Define color coding methods.

##### **Part – C**

(6marks)

1. What is metadata? List out the different types of tags used in html.
2. Explain in detail about <body> tag with neat examples.
3. What is Color tag? List out hexacode values used in the Html?



4. Describe in detail about attributes tags used in html with Example.
5. Explain in detail about the different types of lists with suitable example.
6. What is order list? Explain in detail with suitable example.
7. What is Unorder list? Explain in detail with suitable example.
8. Explain about the three types of color coding methods used in Html.
9. Discuss about the various types of Attributes used in html.
10. Write an html program to create a Resume using of all basic tags.



**KARPAGAM ACADEMY OF HIGHER EDUCATION**  
**COIMBATORE - 21**

**DEPARTMENT OF COMPUTER SCIENCE,CA & IT**

**CLASS : II B.Sc COMPUTER SCIENCE**

**BATCH : 2017-2020**

**Part -A Online Examinations**  
**SUBJECT: HTML Programming**

**(1 mark questions)**  
**SUBJECT CODE: 17CSU404A**

S.No	Question	opt 1	opt 2	opt 3	opt 4	ANSWER
1	HTML stands for _____	Hyper text Markup	Hyperlink Text markup	Hyper Text Markup	Hyper Text Mkarkedup	Hyperlink Text markup Language
2	HTML is known as _____	platform dependant	platform independent	place dependent	place independent	platform independent
3	_____ are used to markup HTML elements	HTML tags	HR tags	head tags	SGML tags	HTML tags
4	what is meant by meta data?	data from data	data about data	data about set	data from link	data about data
5	A _____ element is used to define style information for single	tilte	set	style	character	style
6	The _____ element is used to specify which character set is	meta	link	style	title	meta
7	URL is abbreviated as _____	Uni Resource Location	Uniform Resource	Uniform Resource	Uniform Research	Uniform Resource Locater
8	How many levels of heading elements are in HTML	6	3	7	8	6
9	how many attributes are in HTML?	12	3	5	4	2
10	_____ tag are used to break up sections of a document	line break	horizontal line	preserve	heading	horizontal line
11	the _____ tag creates a line from current position the document to	 	<hr>	<b>	<pre>	<hr>
12	<pre> tag is used for _____	font color	alignment	formatting	links	formatting
13	_____ are very important to give good look and fel to the website	colors	images	font colors	fonts	colors
14	How many<body>tags are in attributes which is used to set	4	3	7	5	5
15	_____ is used to set a color for active links or for selective links	Vlink	link	Alink	text	Alink
16	_____ is used to set a color for visited link that is linked text	Vlink	Alink	link	text	Vlink
17	_____ is used to set a color for linked text	Vlink	Alink	link	text	link
18	_____ sets a color for the back-ground of the page	bg color	Alink	Vlink	text	bg color

19	_____ sets a color for the body text.	text	vlink	Alink	bgcolor	text
20	How many methods are there to set color in web page?	3	5	8	7	3
21	What are there methods to set color in web page ? _____	color name,color	color name,color	color name,color	color font,color	color name,color decimal,hex codes
22	_____ can specify colors directly like green,blue,red.	color name	color decimal	font color	bgcolor	color name
23	A _____ Digit code representing the amount of red,	6	5	7	3	6
24	_____ is specified using the rgb property.	percentage values	percentage decimal	percentage method	percentage	percentage values
25	Color decimal is also known as _____	percentage values	percentage decimal	percentage method	percentage	percentage values
26	Hexa decimal code will proceed by _____	Sigma or hash sign	pound or hash sign	pound or euro	hash sign or euro	pound or hash sign
27	HTML property takes _____ one for red, green and blue.	5 values	3 values	2 values	4 values	3 values
28	rgb values can be an integer between _____	0 to 255 or %	0 to 256 or %	0 to 265 or %	0 to 275 or %	0 to 255 or %
29	All the browsers does not support _____ properties of color.	rgb	rcb	rby	rrb	rgb
30	_____ is used to define the characters of an HTML element.	attribute	links	font color	Vlink	attribute
31	How many categories are in core attributes ? _____	3	4	5	6	4
32	What are core attributes ? _____	id,title,class,style	id,calss,style,head	id,class,link,style	id,head,link,class	id,title,class,style
33	_____ of HTML tag can be used to uniquely identify _____	id attribute	class attribute	style attribute	title attribute	id attribute
34	The value is what you want to the value of the property to set always _____	" "	?	#	=	" "
35	_____ gives a suggested title for the element.	id attribute	title attribute	class attribute	style attribute	title attribute
36	_____ attribute allows you to specify css rules within the _____	style	id	head	font	style
37	css is abbreviated as _____.	cascading style sheet	cascading style script	cascading script style	control style sheet	cascading style sheet
38	The _____ is used to associate an element with a single _____	class attribute	id attribute	title attribute	head attribute	class attribute
39	How many type of list is there in HTML? _____.	2	3	4	5	3
40	What are list in HTML? _____	ordered, unordered,	ordered, preordered,	definition, unordered,	definition, nested,	ordered,unordered, definition
41	_____ offers web authors three ways for specifying list of _____	SGML	HTML	XML	HTTP	HTML
42	_____ will contain list of items using plain bullets.	ordered list	unordered list	definition list	nested list	unordered list

43	An unordered list is a _____ of related	collection	set	order	unordered	collection
44	Each item in the list is marked with _____.	bullets	numeric	hash sign	pound	bullets
45	_____ were created by unordered list.	type attribute	id attribute	style attribute	core attribute	type attribute
46	_____ tag is used to create a unordered list.	<UL>	<OL>	<LI>	<DT>	<UL>
47	_____ tag is used to create a ordered list.	<UL>	<OL>	<LI>	<DT>	<OL>
48	Ordered list is used for the purpose of _____ representation.	numeric	alphabet	symbols	heading	numeric
49	Unordered list is used for the purpose of _____	symbols and bullets	alphabet and numeric	numeric and symbols	heading and symbols	symbols and bullets
50	HTML supports a list style which is called as _____.	definition list	nested list	unordered list	ordered list	definition list
51	_____ list where entires are listed like a dictionary	definition list	nested list	unordered list	ordered list	definition list
52	Defination list makes use of now many tags _____	8	3	5	4	3
53	A _____ list is a idealed way to present a glossary list of the	defination	nested	ordered	unordered	definition
54	<DT> tag is used for __ in defination list	style	links	heading	paragraph	heading
55	<DD> tag is used for _____ in defination list	style	links	heading	paragraph	paragraph
56	<li> tag is used to define the list item	<OL>	<LL>	<LI>	<UL>	<LI>
57	<DT> tag is known as	defination transfer	defination term	definition task	definition text	defination term
58	<DD> tag is known as	defination data	defination term	definition device	definition disk	defination data
59	Give a code for inserting a square in<UL> tags	<UL type="square">	<UL type="square">	<UL type="square">	"<UL type=square">	<UL type="square">
60	Give a code for inserting alphabets in caps in the ordered	<OL Type ="A">	<"OL Type =A">	<OL Type ="A">	<"OL Type ="A">	<OL Type ="A">

## UNIT-II

### SYLLABUS

**Links: Introduction:** Relative Links, Absolute Links, Link Attributes, Using the ID Attribute to Link within a Document

A webpage can contain various links that take you directly to other pages and even specific parts of a given page. These links are known as hyperlinks.

Hyperlinks allow visitors to navigate between Web sites by clicking on words, phrases, and images. Thus you can create hyperlinks using text or images available on a webpage.

- Use the **<a>** element to define a link
- Use the **href** attribute to define the link address
- Use the **target** attribute to define where to open the linked document
- Use the **<img>** element (inside **<a>**) to use an image as a link
- Use the **id** attribute (**id="value"**) to define bookmarks in a page
- Use the **href** attribute (**href="#value"**) to link to the bookmark

### **Linking Documents**

A link is specified using HTML tag **<a>**. This tag is called **anchor tag** and anything between the opening **<a>** tag and the closing **</a>** tag becomes part of the link and a user can click that part to reach to the linked document. Following is the simple syntax to use **<a>** tag.

```
<a href = "Document URL" ... attributes-list>Link Text</a>
```

Example

```
<html>
```

```
<head>
  <title>Hyperlink Example</title>
</head>
<body>
  <p>Click following link</p>
  <a href = "https://www.tutorialspoint.com">Tutorials Point</a>
</body>
</html>
```

### The target Attribute

We have used target attribute in our previous example. This attribute is used to specify the location where linked document is opened. Following are the possible options –

Sr.No	Option	Description
1	_blank	Opens the linked document in a new window or tab.
2	_self	Opens the linked document in the same frame.
3	_parent	Opens the linked document in the parent frame.
4	_top	Opens the linked document in the full body of the window.
5	targetframe	Opens the linked document in a named targetframe.

### Example

Try following example to understand basic difference in few options given for target attribute.

```
<html>
<head>
```

```
<title>Hyperlink Example</title>
<base href = "https://www.tutorialspoint.com/">
</head>
<body>
  <p>Click any of the following links</p>
  <a href = "/html/index.htm" target = "_blank">Opens in New</a> |
  <a href = "/html/index.htm" target = "_self">Opens in Self</a> |
  <a href = "/html/index.htm" target = "_parent">Opens in Parent</a> |
  <a href = "/html/index.htm" target = "_top">Opens in Body</a>
</body>
</html>
```

## HTML Links - Create a Bookmark

HTML bookmarks are used to allow readers to jump to specific parts of a Web page.

Bookmarks can be useful if your webpage is very long.

To make a bookmark, you must first create the bookmark, and then add a link to it.

When the link is clicked, the page will scroll to the location with the bookmark.

Example

First, create a bookmark with the id attribute:

```
<h2 id="C4">Chapter 4</h2>
```

Then, add a link to the bookmark ("Jump to Chapter 4"), from within the same page:

```
<a href="#C4">Jump to Chapter 4</a>
```

Or, add a link to the bookmark ("Jump to Chapter 4"), from another page:

Example

```
<a href="html_demo.html#C4">Jump to Chapter 4</a>
```

```
<!DOCTYPE html>
```

```
<html>
<body>
<p><a href="#C4">Jump to Chapter 4</a></p>
<h2>Chapter 1</h2>
<p>This chapter explains ba bla bla</p>
<h2>Chapter 2</h2>
<p>This chapter explains ba bla bla</p>
<h2>Chapter 3</h2>
<p>This chapter explains ba bla bla</p>
<h2 id="C4">Chapter 4</h2>
<p>This chapter explains ba bla bla</p>
<h2>Chapter 5</h2>
<p>This chapter explains ba bla bla</p>
<h2>Chapter 6</h2>
<p>This chapter explains ba bla bla</p>
<h2>Chapter 7</h2>
<p>This chapter explains ba bla bla</p>
<h2>Chapter 8</h2>
<p>This chapter explains ba bla bla</p>
<h2>Chapter 9</h2>
<p>This chapter explains ba bla bla</p>
<h2>Chapter 10</h2>
<p>This chapter explains ba bla bla</p>
<h2>Chapter 11</h2>
<p>This chapter explains ba bla bla</p>
<h2>Chapter 12</h2>
<p>This chapter explains ba bla bla</p>
<h2>Chapter 13</h2>
```

```
<p>This chapter explains ba bla bla</p>
<h2>Chapter 14</h2>
<p>This chapter explains ba bla bla</p>
<h2>Chapter 15</h2>
<p>This chapter explains ba bla bla</p>
<h2>Chapter 16</h2>
<p>This chapter explains ba bla bla</p>
<h2>Chapter 17</h2>
<p>This chapter explains ba bla bla</p>
</body>
</html>
```

### Linking to a Page Section

You can create a link to a particular section of a given webpage by using **name** attribute. This is a two-step process.

**Note** – The *name* attribute deprecated in HTML5. Do not use this attribute. Use *id* and *title* attribute instead.

First create a link to the place where you want to reach with-in a webpage and name it using `<a...>` tag as follows –

```
<h1>HTML Text Links <a name = "top"></a></h1>
```

Second step is to create a hyperlink to link the document and place where you want to reach –

```
<a href = "/html/html_text_links.htm#top">Go to the Top</a>
```

This will produce following link, where you can click on the link generated **Go to the Top** to reach to the top of the HTML Text Link tutorial.

[Go to the Top](#)



## Local Links

The example above used an absolute URL (A full web address).

A local link (link to the same web site) is specified with a relative URL (without http://www....).

### Example

```
<a href="html_images.asp">HTML Images</a>
```

## HTML Link Colors

By default, a link will appear like this (in all browsers):

- An unvisited link is underlined and blue
- A visited link is underlined and purple
- An active link is underlined and red

You can change the default colors, by using styles:

### Example

```
<style>
```

```
a:link {
```

```
    color: green;
```

```
    background-color: transparent;
```

```
    text-decoration: none;
```

```
}
```

```
a:visited {
```

```
    color: pink;
```

```
    background-color: transparent;
```

```
    text-decoration: none;
```

```
}
```

```
a:hover {
```

```
    color: red;
```

```
    background-color: transparent;
```

```
    text-decoration: underline;
```

```
}  
a:active {  
    color: yellow;  
    background-color: transparent;  
    text-decoration: underline;  
}  
</style>  
</head>  
<body>  
<p>You can change the default colors of links</p>  
<a href="html_images.asp" target="_blank">HTML Images</a>  
</body>  
</html>
```

### Setting Link Colors

You can set colors of your links, active links and visited links using **link**, **alink** and **vlink** attributes of <body> tag

#### Example

Save the following in test.htm and open it in any web browser to see how link, alink and vlink attributes work.

```
<html>  
    <head>  
        <title>Hyperlink Example</title>  
        <base href = "https://www.tutorialspoint.com/">  
    </head>  
    <body alink = "#54A250" link = "#040404" vlink = "#F40633">  
        <p>Click following link</p>  
        <a href = "/html/index.htm" target = "_blank" >HTML Tutorial</a>
```

```
</body>
```

```
</html>
```

This will produce the following result. Just check color of the link before clicking on it, next check its color when you activate it and when the link has been visited.

Click following link

[HTML Tutorial](#)

## Download Links

You can create text link to make your PDF, or DOC or ZIP files downloadable. This is very simple; you just need to give complete URL of the downloadable file as follows:

### Example

```
<html>
```

```
<head>
```

```
<title>Hyperlink Example</title>
```

```
</head>
```

```
<body>
```

```
<a href="http://www.tutorialspoint.com/page.pdf">Download PDF File</a>
```

```
</body>
```

```
</html>
```

This will produce following link and will be used to download a file.

Download PDF File

### ABSOLUTE LINK IN HTML

A link is an absolute link if the URL and file name can be found from anywhere on the Web, not just from a single Web site. An absolute link specifies a fully-qualified URL; the protocol must be present in addition to a domain name, and often a file name must be included as well.

## Relative vs. Absolute Links

A link is an **absolute link** if the URL and file name can be found from anywhere on the Web, not just from a single Web site. An absolute link specifies a fully-qualified URL; the protocol must be present in addition to a domain name, and often a file name must be included as well.

### *Absolute Paths*

- `http://www.mysite.com`
- `http://www.mysite.com/graphics/image.png`
- `http://www.mysite.com/help/articles/how-do-i-set-up-a-webpage.html`

example:

- `<a href="http://www.coffeecup.com">Click here to visit CoffeeCup Software.</a>`
- You *must* use absolute paths when linking to another Website, but you can also use absolute paths within your own website.

A **relative link** specifies the name of the file to be linked to only as it is related to the current document.

### *Relative Paths*

- `index.html`
- `/graphics/image.png`
- `/help/articles/how-do-i-set-up-a-webpage.html`

Example

Here

`http://www.website.com` domain had a subfolder called **pictures**. Inside the pictures folder is a file called **pictures.html**. The full path to this page would be:

`"http://www.website.com/pictures/pictures.html"`

Still with us? Good. Let's say in this `pictures.html` file, we have a link:

### **Difference between an absolute and a relative URL**

An absolute URL contains more information than a relative URL does. Relative URLs are more convenient because they are shorter and often more portable. However, you can use them only to reference links on the same server as the page that contains them.

### **Linking with absolute URLs**

An absolute URL typically takes the following form:

```
protocol://domain/path
```

The protocol is usually `http://`, but can also be `https://`, `ftp://`, `gopher://`, or `file://`. The domain is the name of the website. For example, the domain name of Indiana University's central web server is `www.indiana.edu`. The path includes directory and file information. You must use absolute URLs when referring to links on different servers.

### **Linking with relative URLs**

Relative URLs can take a number of different forms. When referring to a file that occurs in the same directory as the referring page, a URL can be as simple as the name of the file. For example, if you want to create a link in your home page to the file `foobar.html`, which is in the same directory as your home page, you would use:

```
<a href="foobar.html">The Wonderful World of Foobar!</a>
```

If the file you want to link to is in a subdirectory of the referring page's directory, you need to enter only the directory information and the name of the file. So if `foobar.html` were in the `foobar` subdirectory of your `www` directory, you could refer to it from your home page by using:

```
<a href="foobar/foobar.html">The Wonderful World of Foobar!</a>
```

If the file you want to link to is in a higher directory than the referring page, use `..`, which means to go up a directory. For example, to link from `foobar.html` to `home.html`, which is in the directory above, you would use:

```
<a href="../home.html">Go back to my home page</a>
```

## HTML Global Attributes

Attribute	Description
accesskey	Specifies a shortcut key to activate/focus an element
class	Specifies one or more classnames for an element (refers to a class in a style sheet)
contenteditable	Specifies whether the content of an element is editable or not
contextmenu	Specifies a context menu for an element. The context menu appears when a user right-clicks on the element
data-*	Used to store custom data private to the page or application
dir	Specifies the text direction for the content in an element
draggable	Specifies whether an element is draggable or not
dropzone	Specifies whether the dragged data is copied, moved, or linked, when dropped
hidden	Specifies that an element is not yet, or is no longer, relevant
id	Specifies a unique id for an element
lang	Specifies the language of the element's content
spellcheck	Specifies whether the element is to have its spelling and grammar checked or not
style	Specifies an inline CSS style for an element
tabindex	Specifies the tabbing order of an element
title	Specifies extra information about an element
translate	Specifies whether the content of an element should be translated or not

### Attribute definitions

**name = cdata [CS]**

This attribute names the current anchor so that it may be the destination of another link. The value of this attribute must be a unique anchor name. The scope of this name is the current document. Note that this attribute shares the same name space as the id attribute.

Eg: <A name="anchor-one">This is the location of anchor one.</A>

**href = uri [CT]**

This attribute specifies the location of a Web resource, thus defining a link between the current element (the source anchor) and the destination anchor defined by this attribute.

Eg: <A href="http://www.w3.org/">W3C Web site</A>.

**hreflang = langcode [CI]**

This attribute specifies the base language of the resource designated by href and may only be used when href is specified.

**type = content-type [CI]**

This attribute gives an advisory hint as to the content type of the content available at the link target address. It allows user agents to opt to use a fallback mechanism rather than fetch the content if they are advised that they will get content in a content type they do not support.

Authors who use this attribute take responsibility to manage the risk that it may become inconsistent with the content available at the link target address.

For the current list of registered content types, please consult [MIMETYPES].

**rel = link-types [CI]**

This attribute describes the relationship from the current document to the anchor specified by the href attribute. The value of this attribute is a space-separated list of link types.

Eg: <HTML>  
<HEAD>  
<TITLE>Chapter 2</TITLE>

```
<LINK rel="Index" href="../index.html">
<LINK rel="Next" href="Chapter3.html">
<LINK rel="Prev" href="Chapter1.html">
</HEAD>
```

### rev = link-types [CI]

This attribute is used to describe a reverse link from the anchor specified by the href attribute to the current document. The value of this attribute is a space-separated list of link types.

### Forward and reverse links

The **rel** and **rev** attributes play complementary roles -- the rel attribute specifies a forward link and the rev attribute specifies a reverse link.

Consider two documents A and B.

Document A: <LINK href="docB" rel="foo">

Has exactly the same meaning as:

Document B: <LINK href="docA" rev="foo">

Both attributes may be specified simultaneously.

### charset = charset [CI]

This attribute specifies the character encoding of the resource designated by the link. Please consult the section on character encodings for more details.

Attributes defined elsewhere

- id, class (document-wide identifiers)
- lang (language information), dir (text direction)
- title (element title)
- style (inline style information)
- shape and coords (image maps)
- onfocus, onblur, onclick, ondblclick, onmousedown, onmouseup, onmouseover, onmousemove, onmouseout, onkeypress, onkeydown, onkeyup (intrinsic events)
- tabindex (tabbing navigation)
- accesskey (access keys)
- In the following example, we use the hreflang attribute to tell search engines where to find Dutch, Portuguese, and Arabic versions of a document. Note the use of



the charset attribute for the Arabic manual. Note also the use of the lang attribute to indicate that the value of the title attribute for the LINK element designating the French manual is in French.

<HEAD>

<TITLE>The manual in English</TITLE>

<LINK title="The manual in Dutch"

type="text/html"

rel="alternate"

hreflang="nl"

href="http://someplace.com/manual/dutch.html">

<LINK title="The manual in Portuguese"

type="text/html"

rel="alternate"

hreflang="pt"

href="http://someplace.com/manual/portuguese.html">

<LINK title="The manual in Arabic"

type="text/html"

rel="alternate"

charset="ISO-8859-6"

hreflang="ar"

href="http://someplace.com/manual/arabic.html">

<LINK lang="fr" title="La documentation en Fran&ccedil;ais"

type="text/html"

rel="alternate"

hreflang="fr"

href="http://someplace.com/manual/french.html">

</HEAD>

## HTML Email Tag

HTML `<a>` tag provides you option to specify an email address to send an email. While using `<a>` tag as an email tag, you will use **mailto: email address** along with *href* attribute. Following is the syntax of using **mailto** instead of using http.

```
<a href= "mailto: abc@example.com">Send Email</a>
```

This code will generate the following link which you can use to send email.

Send Email

Now, if a user clicks this link, it launches one Email Client (like Lotus Notes, Outlook Express etc. ) installed on your user's computer. There is another risk to use this option to send email because if user do not have email client installed on their computer then it would not be possible to send email.

**Possible Questions**

**Unit-II**

**Part – A**

(1 Mark)

(Online Questions)

**Part -B**

(2 Marks)

1. Define href.
2. What is meant by name attribute?
3. Define alink.
4. Define vlink.
5. What is meant by link?
6. Explain core attribute.
7. What are the values of target attribute?
8. What is target attribute?
9. What is a relative link?
10. What is href attribute?

**Part- C**

(6 marks)

1. Explain in detail about link with an example program.
2. Write about the attributes of <a> tag.
3. What is link? Explain about absolute link with an example.
4. Explain about ID attribute to link within a document.
5. Write about the attributes of <a> tag with an example.
6. What are the various kinds of linking available in HTML? Explain with examples.
7. Explain about how to use styling links in a web page.

**KARPAGAM ACADEMY OF HIGHER EDUCATION**

**COIMBATORE - 21**

**DEPARTMENT OF COMPUTER SCIENCE,CA & IT**

**CLASS : II B.Sc COMPUTER SCIENCE**

**BATCH : 2017-2020**

**Part -A Online Examinations**

**(1 m**

**SUBJECT: HTML Programming**

**SUB:**

S.no	Questions	opt1	opt2
1	Use the _____ element to define a link	<a>	href
2	Use the _____ attribute to define the link address.	<a>	href
3	Use the _____ attribute to define where to open the linked document.	target	id
4	Use the _____ element to use an image as a link.	image	img
5	Use the _____ attribute to define bookmarks in a page.	value	id
6	Use the _____ attribute to link to the bookmark.	target	href
7	A link is specified using HTML tag <a> is called _____.	attribute	anchor
8	_____ opens the linked document in a new window or tab.	_self	_parent
9	_____ Opens the linked document in the same frame.	_parent	_self
10	_____ opens the linked document in the parent frame.	_self	_parent
11	_____ opens the linked document in the full body of the window.	targetfram	_body
12	_____ opens the linked document in a named targetframe.	targetfram	_body
13	You can create a link to a particular section of a given webpage by using _____.	weblink	name
14	An _____ link is underlined and blue.	unvisited	visited
15	A _____ link is underlined and purple.	unvisited	visited

16	An _____ link is underlined and red.	unvisited	visited
17	You can change the default colors by using _____	link	colors
18	An _____ link specifies a fully_qualified URL.	visited	unvisited
19	A _____ link specifies the name of the file to be linked to only as it	relative	absolute
20	Inside the pictures folder is a file called _____.	subfolders	pictures
21	_____ Specifies a shortcut key to activate/focusan element.	class	accesskey
22	_____ Specifies one or more classnames for an element.	class	accesskey
23	_____ Specifies whether the content of an element is editable or no	draggable	dir
24	_____ Used to store custom data private to the page or application.	draggable	data-*
25	_____ Specifies the text direction for the content in an element.	draggable	data-*
26	_____ Specifies whether an elemnt is draggable or not.	draggable	data-*
27	_____ Specifies whether the dragged data is copied, moved, or link	draggable	dropzone
28	_____ Specifies that an element is not yet,or is no longer, relevant.	draggable	dropzone
29	_____ Specifies a unique id for an element.	draggable	dropzone
30	_____ Specifies the language of the element's content.	style	language
31	_____ Specifies an inline CSS style for an element.	inline	style
32	_____ Specifies the tabbing order of an element.	style	tabindex
33	_____ Specifies extra information about an element.	style	tabindex
34	_____ Specifies whether th content of an element should be transla	style	translate
35	HTML _____ tag provides you option to specify an email address to se	</a>	<a>
36	_____ Specifies whether the element is to have its spelling and gra	draggable	spellcheck
37	_____ URLs can take a number of different forms.	absolute	relative

38	A local link is specified with a _____ URL.	absolute	link
39	The _____ attribute deprecated in HTML5.	absolute	link
40	_____ are used to allow readers to jump to specific parts of a V	links	HTML bo
41	The _____ attribute is used to specify the location where linked docu	link	target
42	There are _____ types of links.	1	2

mark questions)

JECT CODE: 17CSU404A

opt3	opt4	Answer
target	</a>	<a>
target	</a>	href
<a>	href	target
<img>	<image>	<img>
href	link	id
link	<a>	href
absolute	hyperlinks	anchor
_blank	_top	_blank
blank	top	self
_blank	_top	_parent
_top	_blank	_top
_top	_blank	targetframe
page	title	name
active	inactive	unvisited
active	inactive	visited

active	inactive	active
default	styles	default
absolute	active	absolute
visited	default	relative
pictures.h	images	pictures.html
data	dropzone	accesskey
data	dropzone	class
contextme	contented	contenteditable
contextme	dir	data-*
contextme	dir	dir
contextme	dir	draggable
hidden	id	dropzone
hidden	id	hidden
hidden	id	id
lang	element	lang
language	element	style
tab	title	tabindex
tab	title	title
spellcheck	title	translate
<td>	<href>	<a>
grammar	lang	spellcheck
name	index	relative



name	index	relative
name	index	name
HTML link	jump	HTML bookmarks
relative	name	target
3	4	2

**UNIT-III**

**SYLLABUS**

**Images:** Putting an Image on a Page, Using Images as Links, Putting an Image in the Background

Images are very important to beautify as well as to depict many complex concepts in simple way on your web page. This tutorial will take you through simple steps to use images in your web pages.

**Insert Image**

You can insert any image in your web page by using <img> tag. Following is the simple syntax to use this tag.

```

```

The <img> tag is an empty tag, which means that, it can contain only list of attributes and it has no closing tag.

**Example**

```
<!DOCTYPE html>
<html>
<head>
<title>Using Image in Webpage</title>
</head>
<body>
<p>Simple Image Insert</p>

</body>
</html>
```

You can use PNG, JPEG or GIF image file based on your comfort but make sure you specify correct image file name in src attribute. Image name is always case sensitive.

The alt attribute is a mandatory attribute which specifies an alternate text for an image, if the image cannot be displayed.

### Attributes

Attribute	Value	Description
<u>align</u>	top bottom middle	Not supported in HTML5. Specifies the alignment of an image according to surrounding elements
<u>alt</u>	text	Specifies an alternate text for an image
<u>border</u>	pixels	Not supported in HTML5. Specifies the width of the border around an image
<u>crossorigin</u>	anonymous use- credentials	Allow images from third-party sites that allow cross-origin access to be used with canvas
<u>height</u>	pixels	Specifies the height of an image
<u>hspace</u>	pixels	Not supported in HTML5. Specifies the whitespace on left and right side of an image
<u>ismap</u>	ismap	Specifies an image as a server-side image-map
<u>longdesc</u>	URL	Specifies a URL to a detailed description of an image
<u>sizes</u>		Specifies image sizes for different page layouts

<u>src</u>	URL	Specifies the URL of an image
srcset	URL	Specifies the URL of the image to use in different situations
<u>usemap</u>	#mapname	Specifies an image as a client-side image-map
<u>vspace</u>	pixels	Not supported in HTML5. Specifies the whitespace on top and bottom of an image
<u>width</u>	pixels	Specifies the width of an image

## HTML Images

Images can improve the design and the appearance of a web page.

### HTML Images Syntax

In HTML, images are defined with the **<img>** tag.

The **<img>** tag is empty, it contains attributes only, and does not have a closing tag.

The **src** attribute specifies the URL (web address) of the image:

```

```

```
<!DOCTYPE html>
```

```
<html>
```

```
<body>
```

```

```

```
</body>
```

```
</html>
```

### The alt Attribute

The alt attribute provides an alternate text for an image, if the user for some reason cannot view it (because of slow connection, an error in the src attribute, or if the user uses a screen reader).

The value of the alt attribute should describe the image:

#### Example

```

```

Image Size - Width and Height

You can use the **style** attribute to specify the width and height of an image.

#### Example

```
<!DOCTYPE html>
<html>
<body>



</body>
</html>
```

Width and Height, or Style?

Both the width, height, and style attributes are valid in HTML5.

However, we suggest using the style attribute. It prevents styles sheets from changing the size of images:

#### Example

```
<!DOCTYPE html>
<html>
<head>
<style>
img {
    width:100%;
}
</style>
</head>
<body>



```

```
</body>
```

```
</html>
```

### Set Image Location

Usually we keep all the images in a separate directory. So let's keep HTML file test.htm in our home directory and create a subdirectory images inside the home directory where we will keep our image test.png.

### Example

Assuming our image location is "image/test.png", try the following example:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>Using Image in Webpage</title>
```

```
</head>
```

```
<body>
```

```
<p>Simple Image Insert</p>
```

```

```

```
</body>
```

```
</html>
```

### Set Image Width/Height

You can set image width and height based on your requirement using width and height attributes. You can specify width and height of the image in terms of either pixels or percentage of its actual size.

### Example

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>Set Image Width and Height</title>
```

```
</head>
```

```
<body>
```

<p>Setting image width and height</p>



</body>

</html>

### Set Image Border

By default, image will have a border around it, you can specify border thickness in terms of pixels using border attribute. A thickness of 0 means, no border around the picture.

Example

<!DOCTYPE html>

<html>

<head>

<title>Set Image Border</title>

</head>

<body>

<p>Setting image Border</p>



</body>

</html>

### Set Image Alignment

By default, image will align at the left side of the page, but you can use align attribute to set it in the center or right.

Example

<!DOCTYPE html>

<html>

<head>

<title>Set Image Alignment</title>

</head>

<body>

<p>Setting image Alignment</p>

```

</body>
</html>
```

## HTML – IMAGE LINKS

We have seen how to create hypertext link using text and we also learnt how to use images in our webpages. Now, we will learn how to use images to create hyperlinks.

### Example

It's simple to use an image as hyperlink. We just need to use an image inside hyperlink at the place of text as shown below:

```
<!DOCTYPE html>
<html>
<head>
<title>Image Hyperlink Example</title>
</head>
<body>
<p>Click following link</p>
<a href="http://www.tutorialspoint.com" target="_self">

</a>
</body>
</html>
```

## Mouse-Sensitive Images

The HTML and XHTML standards provides a feature that lets you embed many different links inside a single image. You can create different links on the single image based on different coordinates available on the image. Once different links are attached to different coordinates, we can click different parts of the image to open target documents. Such mouse-sensitive images are known as image maps.

There are two ways to create image maps:



- ☐ **Server-side image maps** - This is enabled by the **ismap** attribute of the <img> tag and requires access to a server and related image-map processing applications.
- ☐ **Client-side image maps** - This is created with the **usemap** attribute of the <img> tag, along with corresponding <map> and <area> tags.

### Server-Side Image Maps

Here you simply put your image inside a hyper link and use ismap attribute which makes it special image and when the user clicks some place within the image, the browser passes the coordinates of the mouse pointer along with the URL specified in the <a> tag to the web server. The server uses the mouse-pointer coordinates to determine which document to deliver back to the browser.

When ismap is used, the href attribute of the containing <a> tag must contain the URL of a server application like a cgi or PHP script etc. to process the incoming request based on the passed coordinates.

The coordinates of the mouse position are screen pixels counted from the upper-left corner of the image, beginning with (0,0). The coordinates, preceded by a question mark, are added to the end of the URL.

```
<!DOCTYPE html>
<html>
<head>
<title>ISMAP Hyperlink Example</title>
</head>
<body>
<p>Click following link</p>
<a href="/cgi-bin/ismap.cgi" target="_self">

</a>
</body>
</html>
```

Then the browser sends the following search parameters to the web server which can be processed by ismap.cgi script or map file and you can link whatever documents you like to these coordinates:

/cgi-bin/ismap.cgi?20,30

This way you can assign different links to different coordinates of the image and when those coordinates are clicked, you can open corresponding linked document. To learn more about ismap attribute, you can check How to use Image ismap?

**Note:** You will learn CGI programming when you will study Perl programming. You can write your script to process these passed coordinates using PHP or any other script as well. For now, let's concentrate on learning HTML and later you can revisit this section.

### Client-Side Image Maps

Client side image maps are enabled by the usemap attribute of the <img /> tag and defined by special <map> and <area> extension tags.

The image that is going to form the map is inserted into the page using the <img /> tag as a normal image, except it carries an extra attribute called usemap. The value of the usemap attribute is the value which will be used in a <map> tag to link map and image tags. The <map> along with <area> tags define all the image coordinates and corresponding links.

The <area> tag inside the map tag, specifies the shape and the coordinates to define the boundaries of each clickable hotspot available on the image. Here's an example from the image map:


```
<html>
<head>
<title>USEMAP Hyperlink Example</title>
</head>
<body>
<p>Search and click the hotspot</p>
<img src=/images/html.gif alt="HTML Map" border="0" usemap="#html"/>
<!-- Create Mappings -->
<map name="html">
```

```
<area shape="circle"
coords="80,80,20" href="/css/index.htm" alt="CSS Link" target="_self" />
<area shape="rect"
coords="5,5,40,40" alt="jQuery Link" href="/jquery/index.htm" target="_self" />
</map>
</body>
```

### Add a Background Image to a Custom HTML

If you want to add an image to a web page, all you need is HTML. If you'd like to set an image as a background to a web page, you'll need both HTML and CSS. HTML stands for Hypertext Markup Language and is code that tells a browser what to show on a web page.[1] CSS stands for Cascading Style Sheets and is used to change the appearance and layout of a web page.[2] You'll need a background image that you'd like to use for your web page.


### Setting Up Your Files



**Create a folder to hold your HTML file and background image.**

On your computer, create and name a folder that you can easily find later.


You can name the folder anything you like, but when working with HTML, it's best to get in the habit of naming files and folders with short, single word names.



**Put the background image into the HTML folder.** Put the image you'd like to use as background into the HTML folder.

If you aren't too concerned with ensuring your website will run well on older devices with slower internet connections, you should be safe in using a higher resolution image as your background. Simple images with light, repetitive patterns are also a good choice when deciding on a background image so that you can read any text on top of it.

If you don't have an image, you can download a free background image. If you download an image, put it in the HTML folder you created.




**Create an HTML file.** Open a text editor, and then create a new file. Save the file as index.html.

You can use any text editor you want, even the system text editors provided by Windows, Notepad, and Mac OS X, TextEdit.

If you want to use a text editor intended for working with HTML, click here to download Atom, a text editor that works on Windows, Mac OS X, and Linux operating systems.

If you're using TextEdit, before starting to write the HTML file, click the Format menu, and then click Make Plain Text. This setting will make sure the HTML file loads properly in a web browser.


Word processors, such as Microsoft Word, are not great for writing HTML, because they add invisible characters and formatting that can break an HTML file so that it doesn't display correctly in a web browser.



**Copy and paste the standard HTML code.** Select and copy the HTML code below, and then paste it into your open index.html file.

```
<!DOCTYPE html>
<html>
<head>
<title>Page Title</title>
<style>
body {
    background-image: url(" ");
}
</style>
</head>
<body>
</body>
</html>
```





**Possible Questions**  
**Unit-III**

**Part –A** (1 mark)  
(Online Questions)

**Part –B** (2 Marks)

1. Define <img> tag.
2. What are the attributes of <img> tag?
3. What is src attribute?
4. What is the use of alt?
5. How to set the width and height of image size?
6. What is a relative link?
7. What is an absolute link?
8. Differentiate between any two steps of relative link and absolute link.
9. What is the ID attributes?

**Part –C** (6 Marks)

1. List out any five types of attributes used in the <img> tag and explain it.
2. Discuss about the two ways of image maps to create a link with suitable example.
3. Elaborate in detail about client side image map with an example.
4. Explain about the different steps to insert image in the background page.
5. Elaborate in detail about server side image map with an example.
6. Write a HTML program to insert an image in the table.
7. List out any five types of core attributes used in the html and explain it.
8. Explain about the different steps to insert image in the background page.



**KARPAGAM ACADEMY OF HIGHER EDUCATION****COIMBATORE - 21****DEPARTMENT OF COMPUTER SCIENCE,CA & IT****CLASS : II B.Sc COMPUTER SCIENCE****BATCH : 2017-2020****Part -A Online Examinations****(1 mark questions)****SUBJECT: HTML Programming****SUBJECT CODE: 17CSU404A**

S.No	QUESTION	OPTION 1	OPTION 2	OPTION 3	OPTION 4	ANSWER
1	Images in GIF format is commonly used in	Image format	Web pages	PNG images	obtaining images	web pages
2	To place an image in an HTML document use the	<Title>	<Body>	<Img>	 	<img>
3	The _____ attributes specifies the source of the image using a URL	ID	SVC	Style	Title	SVC
4	The _____ attribute is the perhaps the most important because it provides alternate text	alt	id	SVC	title	alt
5	In recent browser _____ text also displays as a tppl tip when the cursor passes over the image	alt	id	SVC	ttle	alt
6	The _____ and _____ attributes also be used to resize images	Height,width	SVC,URL	KB OR MB	Aspect ration	height and width
7	The _____ attributes determines an images position relative to text flow and other content	id	svc	align	title	align
8	The _____ and _____ attributes creates harizontal and vertical space around the images	pixels	vspace,hspac e	id,img	img,br	vspace,hspace
9	Images may also be used as background images for html documents by using the attributes	style	title	backgroun d	href	background

10	The _____ elements can be placed within the<a> element to create graphic hyperlink	<p>	<hi>	<div>	<img>	<img>
11	A nonlinked images will not display a border unless the _____ to the desired width	border	pixels	align	PNG	border
12	Images can be used to the create multiple links in a _____	single image	double image	bg image	image source	single image
13	Background color by using the tag called _____	BG Color	 	<HTML>	<head>	BG Color
14	To define an image as an image map use the _____ attributes	<map>	<object>	usemap	imagemap	usemap
15	The image format are _____	JPEG,PNG, APNG	JPEG,GIF,P NG	AVI,CSS, DOC	EXE,HTML, MIDI	JPEG,GIF,PNG
16	_____ are used in the ONG or GIF	smallest dimension	height and width	max width	C SS image scale	smallest dimension
17	_____ attributes is used to control the background of an HTML element	<bg color>	<HTML>	href	id	BG Color
18	_____ is described mathematically as a set of curves	vector image	GIF	moving images	JPEG compression	vector image
19	Image compression depends on the _____	EXE,HTML, MIDI	File format	image file format	img,br	image file format
20	Complex background image tend to be _____.	good design	poor design	bgcolor	web page	poor design
21	You can give space on both sides of the image using the tags called _____ and _____.	pixels	id.img	img.br	vspace and nepace	vspace and nepace
22	We can change the height and width of the image in terms of _____.	pixels	title	layout	webpages	pixels
23	To wrap the text around image we use the tag called _____.	align	srcset	wemap	vspace	align

24	_____ is an empty element and it used to insert and incrisible region.	cheek box	force layout	<hidden>	browser	force layout
25	The _____ attributes may also be set to provide adivsory text about what the image is.	<body>	<title>	<img>	 	<title>
26	The <figcaption> tag defines a caption for a _____ element.	<tagname>	<figure>	start tag	content	<figure>
27	The background color set a _____ for the entire document.	page color	solid color	bgcolor attribute	background color property	solid color
28	The background color of HTML page is _____.	blue	green	white	black	white
29	BGcolor is the _____.	HTML attribute	web address	default funtionalit y	attribute	HTML attribute
30	_____ sets whether the background image is forced or scrool with rest of the page.	background attachment	form attachment	input accept attachment	attachment property.	background attachment
31	_____ are very important to give good look and feel to website.	color	image	design	background	color
32	_____ sets a color for linked list.	Alink	link	Vlink	text	link
33	_____ sets a color for active link.	Alink	link	Vlink	text	Alink
34	_____ set a color for body text.	Alink	link	Vlink	text	text
35	_____ set a color for a visited links.	Alink	link	Vlink	text	Vlink

**UNIT-IV**

**SYLLABUS**

**Creating: Table, Table Headers, Captions, Spanning Multiple Columns, Styling Table**

The HTML tables allow web authors to arrange data like text, images, links, other tables, etc. into rows and columns of cells.

The HTML tables are created using the **<table>** tag in which the **<tr>** tag is used to create table rows and **<td>** tag is used to create data cells.

**Example**

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Tables</title>
</head>
<body>
<table border="1">
<tr>
<td>Row 1, Column 1</td>
<td>Row 1, Column 2</td>
</tr>
<tr>
<td>Row 2, Column 1</td>
<td>Row 2, Column 2</td>
</tr>
</table>
</body>
</html>
```

This will produce the following result:

Row 1, Column 1    Row 1, Column 2

Row 2, Column 1    Row 2, Column 2

### Table Heading

Table heading can be defined using **<th>** tag. This tag will be put to replace **<td>** tag, which is used to represent actual data cell. Normally you will put your top row as table heading as shown below, otherwise you can use **<th>** element in any row.

### Example

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Table Header</title>
</head>
<body>
<table border="1">
<tr>
<th>Name</th>
<th>Salary</th>
</tr>
<tr>
<td>Ramesh Raman</td>
<td>5000</td>
</tr>
<tr>
<td>Shabbir Hussein</td>
<td>7000</td>
</tr>
</table>
```

</body>

</html>

This will produce the following result:

Name	Salary
Ramesh Raman	5000
Shabbir	7000
Hussein	

### Cellpadding and Cellspacing Attributes

There are two attributes called *cellpadding* and *cellspacing* which you will use to adjust the white space in your table cells. The cellspacing attribute defines the width of the border, while cellpadding represents the distance between cell borders and the content within a cell.

#### Example

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Table Cellpadding</title>
</head>
<body>
<table border="1" cellpadding="5" cellspacing="5">
<tr>
<th>Name</th>
<th>Salary</th>
</tr>
<tr>
<td>Ramesh Raman</td>
<td>5000</td>
</tr>
<tr>
<td>Shabbir Hussein</td>
<td>7000</td>
</tr>
```

```
</tr>
</table>
</body>
</html>
```

This will produce the following result:

Name	Salary
Ramesh Raman	5000
Shabbir Hussein	7000

### Colspan and Rowspan Attributes

You will use **colspan** attribute if you want to merge two or more columns into a single column. Similar way you will use **rowspan** if you want to merge two or more rows.

#### Example

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Table Colspan/Rowspan</title>
</head>
<body>
<table border="1">
<tr>
<th>Column 1</th>
<th>Column 2</th>
<th>Column 3</th>
</tr>
<tr><td rowspan="2">Row 1 Cell 1</td><td>Row 1 Cell 2</td><td>Row 1 Cell
3</td></tr>
<tr><td>Row 2 Cell 2</td><td>Row 2 Cell 3</td></tr>
<tr><td colspan="3">Row 3 Cell 1</td></tr>
</table>
</body>
```

</html>

This will produce the following result:

Column 1	Column 2	Column 3
Row 1 Cell 1	Row 1 Cell 2	Row 1 Cell 3
	Row 2 Cell 2	Row 2 Cell 3
Row 3 Cell 1		

### Tables Backgrounds

You can set table background using one of the following two ways:

- ☐ bgcolor attribute - You can set background color for whole table or just for one cell.
- ☐ background attribute - You can set background image for whole table or just for one cell.

You can also set border color also using **bordercolor** attribute.

### Example

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Table Background</title>
</head>
<body>
<table border="1" bordercolor="green" bgcolor="yellow">
<tr>
<th>Column 1</th>
<th>Column 2</th>
<th>Column 3</th>
</tr>
<tr><td rowspan="2">Row 1 Cell 1</td><td>Row 1 Cell 2</td><td>Row 1 Cell
3</td></tr>
```



```
<tr><td>Row 2 Cell 2</td><td>Row 2 Cell 3</td></tr>
<tr><td colspan="3">Row 3 Cell 1</td></tr>
</table>
</body>
</html>
```

This will produce the following result:

Column 1	Column 2	Column 3
Row 1 Cell 1	Row 1 Cell 2	Row 1 Cell 3
	Row 2 Cell 2	Row 2 Cell 3
Row 3 Cell 1		

Here is an example of using background attribute. Here we will use an image available in /images directory.

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Table Background</title>
</head>
<body>
<table border="1" bordercolor="green" background="/images/test.png">
<tr>
<th>Column 1</th>
<th>Column 2</th>
<th>Column 3</th>
</tr>
```

```
<tr><td rowspan="2">Row 1 Cell 1</td><td>Row 1 Cell 2</td><td>Row 1 Cell
3</td></tr>
<tr><td>Row 2 Cell 2</td><td>Row 2 Cell 3</td></tr>
<tr><td colspan="3">Row 3 Cell 1</td></tr>
</table>
</body>
</html>
```

This will produce the following result. Here background image did not apply to table's header.

Column 1	Column 2	Column 3
Row 1 Cell 1	Row 1 Cell 2	Row 1 Cell 3
	Row 2 Cell 2	Row 2 Cell 3
Row 3 Cell 1		

### Table Height and Width

You can set a table width and height using **width** and **height** attributes. You can specify table width or height in terms of pixels or in terms of percentage of available screen area.

#### Example

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Table Width/Height</title>
</head>
<body>
<table border="1" width="400" height="150">
<tr>
<td>Row 1, Column 1</td>
<td>Row 1, Column 2</td>
</tr>
```

```
<tr>
<td>Row 2, Column 1</td>
<td>Row 2, Column 2</td>
</tr>
</table>
</body>
</html>
```

This will produce the following result:

Row 1, Column 1	Row 1, Column 2
Row 2, Column 1	Row 2, Column 2

### Table Caption

The **caption** tag will serve as a title or explanation for the table and it shows up at the top of the table. This tag is deprecated in newer version of HTML/XHTML.

### Example

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Table Caption</title>
</head>
<body>
<table border="1" width="100%">
<caption>This is the caption</caption>
<tr>
<td>row 1, column 1</td><td>row 1, column 2</td>
</tr>
<tr>
<td>row 2, column 1</td><td>row 2, column 2</td>
</tr>
</table>
```

</body>

</html>

This will produce the following result:

This is the caption	
row 1, column 1	row 1, column 2
row 2, column 1	row 2, column 2

### Table Header, Body, and Footer

Tables can be divided into three portions: a header, a body, and a foot. The head and foot are rather similar to headers and footers in a word-processed document that remain the same for every page, while the body is the main content holder of the table.

The three elements for separating the head, body, and foot of a table are:

- ☐ <thead> - to create a separate table header.
- ☐ <tbody> - to indicate the main body of the table.
- ☐ <tfoot> - to create a separate table footer.

A table may contain several <tbody> elements to indicate different pages or groups of data. But it is notable that <thead> and <tfoot> tags should appear before <tbody>

Example

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Table</title>
</head>
<body>
<table border="1" width="100%">
<thead>
<tr>
<td colspan="4">This is the head of the table</td>
```

```
</tr>
</thead>
<tfoot>
<tr>
<td colspan="4">This is the foot of the table</td>
</tr>
</tfoot>
<tbody>
<tr>
<td>Cell 1</td>
<td>Cell 2</td>
<td>Cell 3</td>
<td>Cell 4</td>
</tr>
</tbody>
</table>
</body>
</html>
```

This will produce the following result:

This is the head of the table			
This is the foot of the table			
Cell 1	Cell 2	Cell 3	Cell 4

### Nested Tables

You can use one table inside another table. Not only tables you can use almost all the tags inside table data tag <td>.

### Example

Following is the example of using another table and other tags inside a table cell.

```
<!DOCTYPE html>
<html>
```

```
<head>

<title>HTML Table</title>

</head>

<body>

<table border="1" width="100%">

<tr>

<td>

<table border="1" width="100%">

<tr>

<th>Name</th>

<th>Salary</th>

</tr>

<tr>

<td>Ramesh Raman</td>

<td>5000</td>

</tr>

<tr>

<td>Shabbir Hussein</td>

<td>7000</td>

</tr>

</table>

</td>

</tr>

</table>

</body>

</html>
```

This will produce the following result:

Name	Salary
Ramesh Raman	5000
Shabbir Hussein	7000

### Styling Table

Styling an HTML table isn't the most glamorous job in the world, but sometimes we have to do it

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<style>
```

```
table, th, td {
```

```
    border: 1px solid black;
```

```
    border-collapse: collapse;
```

```
}
```

```
th, td {
```

```
    padding: 5px;
```

```
    text-align: left;
```

```
}
```

```
table#t01 {
```

```
    width: 100%;
```

```
    background-color: #f1f1c1;
```

```
}
```

```
</style>
```

```
</head>
```

```
<body>
```

```
<table style="width:100%">
```

```
<tr>
```

```
<th>Firstname</th>
<th>Lastname</th>
<th>Age</th>
</tr>
<tr>
<td>Jill</td>
<td>Smith</td>
<td>50</td>
</tr>
<tr>
<td>Eve</td>
<td>Jackson</td>
<td>94</td>
</tr>
<tr>
<td>John</td>
<td>Doe</td>
<td>80</td>
</tr>
</table>
<br>
```

```
<table id="t01">
<tr>
<th>Firstname</th>
<th>Lastname</th>
<th>Age</th>
</tr>
<tr>
<td>Jill</td>
```



```
<td>Smith</td>
<td>50</td>
</tr>
<tr>
<td>Eve</td>
<td>Jackson</td>
<td>94</td>
</tr>
<tr>
<td>John</td>
<td>Doe</td>
<td>80</td>
</tr>
</table>
</body>
</html>
```

**OUTPUT:**

Firstname	Lastname	Age
Jill	Smith	50
Eve	Jackson	94
John	Doe	80

Firstname	Lastname	Age
Jill	Smith	50
Eve	Jackson	94
John	Doe	80

**Possible Questions**

**Unit-IV**

**Part –A**  
(Online Questions)

(1 mark)

**Part –B**

(2 Marks)

1. Write the syntax for creating the table.
2. What is <thead>tag?
3. Write syntax for creating table.
4. Write the syntax for row span.
5. What is tfoot?
6. Write the syntax for colspan.
7. Differentiate rowspan and colspan.
8. Define spanning.
9. What is caption?

**Part –C**

(6 Marks)

1. What are all the tags used in creating a table?
2. Illustrate the creation and manipulation of table with examples accordingly.
3. Explain about creating a table header with a program.
4. Explain in detail about spanning multiple columns.
5. Describe the process of dividing the table into rows and columns?
6. Write a program to create a table using HTML which consists of columns for Roll No., Student's name and grade.
7. Explain in detail about styling table.
8. Create a table for staffs' salary package and perform some manipulations in it accordingly.
9. Explain in detail about spanning multiple rows.
10. Explain in detail about colspan and rowspan with example.

**KARPAGAM ACADEMY OF HIGHER EDUCATION  
COIMBATORE - 21**

**DEPARTMENT OF COMPUTER SCIENCE,CA & IT**

**CLASS : II B.Sc COMPUTER SCIENCE**

**BATCH : 2017-2020**

**Part -A Online Examinations  
SUBJECT: HTML Programming**

**(1 mark questions)  
SUBJECT CODE: 17CSU404A**

S. No	Questions	OPT1	OPT2	OPT3	OPT4	Answer
1	The _____ tag defines a table caption	<table>	<caption>	<style>	none of these	<caption>
2	1. The <caption> tag must be inserted immediately after the	<caption>	<head>	<table>	<title>	<table>
3	The css properties _____ and _____ can be used to align and place the caption	text-align,caption-side	caption-side,text-align	align-text,side-caption	both a&b	<b>both a&amp;b</b>
4	Header information in a table is defined with the _____ tag	<td>	<th>	</td>	<tr>	<th>
5	The caption element can only be used once per table and must	continue	start	end	paused	<b>start</b>
6	The _____ end tag may always be safely omitted	TFOOT	THEAD	TBODY	TITLE	<b>TBODY</b>
7	The _____ tag is not supported in HTML5	<head>	<title>	<body>	<center>	<center>
8	The _____ tag is a phrase tag. It defines a piece of computer	<em>	<strong>	<code>	<samp>	<code>
9	The _____ tag defines a important text	<code>	<strong>	<code>	<samp>	<strong>
10	The _____ tag defines a variable	<samp>	<kbd>	<var>	<strong>	<var>
11	The _____ tag defines a sample output from a computer	<code>	<samp>	<em>	<strong>	<samp>
12	The _____ tag defines a renders as emphasized text	<kbd>	<strong>	<var>	<em>	<em>
13	The _____ tag defines a keyboard input	<code>	<kbd>	<samp>	<strong>	<kbd>
14	_____ defines contact information for the	<applet>	<area>	<a>	address>	<b>address&gt;</b>
15	_____ used to draw graphics, on the fly, via scripting	<caption>	<canvas>	<center>	<cite>	<canvas>
16	The HTML table allow web authors to arrange data	text,image,links.	image,text,links.	links,image,text.	text,links,image	<b>text,image,links.</b>
17	The HTML table are created by using the _____ tag.	<thead>	<caption>	<table>	<sub>	<table>
18	_____ tag is used to create table rows.	<th>	<tr>	<td>	<table>	<tr>

19	If the table content is ambiguous or has both column	id	script	scope	style	<b>scope</b>
20	Table can be divided into portions.	two	one.	seven	three	<b>three</b>
21	What are the three main parts of a table?.	rows,columns,cells	header,body,footer.	columns,rows,cells.	footer,header,body	<b>header,body,footer.</b>
22	_____ using to create a separate table header	<thead>	<th>	<td>	<tr>	<thead>
23	_____ using to indicate the main body of the table	<table>	<thead>.	<tbody>	<tfoot>	<tbody>
24	_____ using to create a separate table footer.	<table>	<thead>	<thead>	<tfoot>	<tfoot>
25	A table may contain several _____ element to	<table>.	<thead>	<tbody>	<tfoot>	<tbody>
26	An HTML table contains a set of	rows and columns	tags	cells	attributes	<b>rows and columns</b>
27	Each row consists of one or more	rows	columns	cells	tags	<b>cells</b>
28	Header information table in a table is defined with the	<th>	<tr>	<td>	<table>	<th>
29	The <th> elements are contained within a	<th>	<tr>	<td>	<table>	<tr>
30	Most _____ make <th> cells content centered and bold.	web pages	table	attributes	browser	<b>browser</b>
31	Cells within HTML tables can span multiple _____	Rows	Columns	Span	Both a & b	<b>Both a &amp; b</b>
32	_____ attribute a cell can span more than one row	Rowspan	Colspan	Rows	All the above	<b>Rowspan</b>
33	Use _____ to extend cells down and _____ to extend	Colspan and rowspan	Attributes and values	Spanning and link	Rowspan and	<b>Rowspan and</b>
34	The _____ element is often used as a container for some	<body>	<table>	<span>	None of these	<span>
35	The value of table attribute is _____	Real number	Whole number	Natural number	Integer	<b>Whole number</b>
36	The _____ is an attribute of <table> tag and it is used to put	Border	Collapse	Table	Span	<b>Border</b>
37	HTML was discovered in	1997	1998	1991	2000	<b>1991</b>
38	_____ defines a term /name in a description list	<embed>	<div>	<dt>	<dl>	<dt>
39	_____ defines information about the document	<head>	<header>	<hr>	<html>	<head>
40	_____ defines the relationship between a document and an	<main>	<li>	<link>	<nav>	<link>
41	_____ defines multiple media resource for media element	<span>	<source>	<select>	<section>	<source>

42	_____ defines a visible heading for a <details> element	<summary>	<style>	<table>	<tbody>	<summary>
43	_____ specifies a list of pre defined option for input controls	<dd>	<data list>	<del>	<details>	<data list>
44	The _____ specifies the width that should appear	Table layout	Border –collapse	Border –spacing	Caption- side	<b>Border –spacing</b>
45	The _____ specifies whether the border should be shown if a	Table layout	Border –collapse	Caption- side	Empty - cells	<b>Empty - cells</b>
46	Use the HTML _____ element to define a table.	<table>	<tr>	<td>	<th>	<table>
47	Use the HTML _____ element to define a table row.	<table>	<tr>	<td>	<th>	<tr>
48	Use the HTML _____ element to define a table data.	<table>	<tr>	<td>	<th>	<td>
49	Use the HTML _____ element to define a table heading.	<table>	<tr>	<td>	<th>	<th>
50	The _____ property sets whether the table borders	coloum-collapse	row-collapse	both a and b	border-collapse	<b>border-collapse</b>
51	Use the _____ property to define a border.	table border	CSS border	border	header	<b>CSS border</b>
52	The technique we’re going to use is explained in detail at _____	CSS tricks	query	explained	none of these	<b>CSS tricks</b>
53	We used the _____ selector to pick out the table body row	odd	even	both a and b	none of these	<b>even</b>
54	We have used the _____ selector to identify the footer row	odd	even	both a and b	none of these	<b>odd</b>
55	It was horrendously tedious since the _____	<body>	<p>	<dt>	<font>	<font>
56	We can clean up that table HTML, add a single class to the	CSS tricks	attribute	constraints	CSS rule set	<b>CSS rule set</b>
57	Words like _____ can be used to target every other child	odd	even	odd or even	none of these	<b>odd or even</b>
58	Next, create a new file called _____ and save it in the same	font.css	stylesheet	style.css	none of these	<b>style.css</b>

**UNIT-V**

**SYLLABUS**

**Forms: Basic** Input and Attributes, Other Kinds of Inputs, Styling forms with CSS, Where to Go from Here

HTML Forms are required, when you want to collect some data from the site visitor. For example, during user registration you would like to collect information such as name, email address, credit card, etc.

A form will take input from the site visitor and then will post it to a back-end application such as CGI, ASP Script or PHP script etc. The back-end application will perform required processing on the passed data based on defined business logic inside the application.

There are various form elements available like text fields, textarea fields, drop-down menus, radio buttons, checkboxes, etc.

The HTML **<form>** tag is used to create an HTML form and it has following syntax:

```
<form action="Script URL" method="GET|POST">
```

form elements like input, textarea etc.

```
</form>
```

**Form Attributes**

Apart from common attributes, following is a list of the most frequently used form attributes:

Attribute	Description
action	Backend script ready to process your passed data.
method	Method to be used to upload data. The most frequently used are GET and POST methods.

target	Specify the target window or frame where the result of the script will be displayed. It takes values like _blank, _self, _parent etc.
enctype	You can use the enctype attribute to specify how the browser encodes the data before it sends it to the server. Possible values are: application/x-www-form-urlencoded - This is the standard method most forms use in simple scenarios. multipart/form-data - This is used when you want to upload binary data in the form of files like image, word file etc.

## HTML Form Controls

There are different types of form controls that you can use to collect data using HTML form:

- ☐ Text Input Controls
- ☐ Checkboxes Controls
- ☐ Radio Box Controls
- ☐ Select Box Controls
- ☐ File Select boxes
- ☐ Hidden Controls
- ☐ Clickable Buttons

- ☐ Submit and Reset Button

### **Text Input Controls**

There are three types of text input used on forms:

- ☐ **Single-line text input controls** - This control is used for items that require only one line of user input, such as search boxes or names. They are created using HTML `<input>` tag.
- ☐ **Password input controls** - This is also a single-line text input but it masks the character as soon as a user enters it. They are also created using HTML `<input>` tag.
- ☐ **Multi-line text input controls** - This is used when the user is required to give details that may be longer than a single sentence. Multi-line input controls are created using HTML `<textarea>` tag.

### **Single-line text input controls**

This control is used for items that require only one line of user input, such as search boxes or names. They are created using HTML `<input>` tag.

### **Example**

Here is a basic example of a single-line text input used to take first name and last name:

```
<!DOCTYPE html>
<html>
<head>
<title>Text Input Control</title>
</head>
<body>
<form >
First name: <input type="text" name="first_name" />
<br>
Last name: <input type="text" name="last_name" />
</form>
```



</body>

</html>

This will produce the following result:

First

name:

Last name:

## Attributes

Following is the list of attributes for <input> tag for creating text field.

Attribute	Description
type	Indicates the type of input control and for text input control it will be set to text.
name	Used to give a name to the control which is sent to the server to be recognized and get the value.
value	This can be used to provide an initial value inside the control.
size	Allows to specify the width of the text-input control in terms of characters.
maxlength	Allows to specify the maximum number of characters a user can enter into the text box.

## Password Input controls

This is also a single-line text input but it masks the character as soon as a user enters it.

They are also created using HTML <input> tag but type attribute is set to password.

Example



Here is a basic example of a single-line password input used to take user password:

```
<!DOCTYPE html>
<html>
<head>
<title>Password Input Control</title>
</head> <body>
<form >
User ID : <input type="text" name="user_id" />
<br>
Password: <input type="password" name="password" />
</form>
</body>
</html>
```

This will produce the following result:

User ID :

Password:

## Attributes

Following is the list of attributes for <input> tag for creating password field.

Attribute	Description
type	Indicates the type of input control and for password input control it will be set to password.
name	Used to give a name to the control which is sent to the server to be recognized and get the value.
value	This can be used to provide an initial value inside the control.

size	Allows to specify the width of the text-input control in terms of characters.
maxlength	Allows to specify the maximum number of characters a user can enter into the text box.

## Multiple-Line Text Input Controls

This is used when the user is required to give details that may be longer than a single sentence. Multi-line input controls are created using HTML `<textarea>` tag.

Example

Here is a basic example of a multi-line text input used to take item description:

```
<!DOCTYPE html>
<html>
<head>
<title>Multiple-Line Input Control</title>
</head>
<body>
<form>
Description: <br />
<textarea rows="5" cols="50" name="description">
Enter description here...
</textarea>
</form>
</body>
</html>
```

This will produce the following result:



## Attributes

Following is the list of attributes for <textarea> tag.

Attribute	Description
name	Used to give a name to the control which is sent to the server to be recognized and get the value.
rows	Indicates the number of rows of text area box.
cols	Indicates the number of columns of text area box

## Checkbox Control

Checkboxes are used when more than one option is required to be selected. They are also created using HTML <input> tag but type attribute is set to checkbox.

Example

Here is an example HTML code for a form with two checkboxes:

```
<!DOCTYPE html>
<html>
<head>
<title>Checkbox Control</title>
</head>
<body>
<form>
<input type="checkbox" name="maths" value="on"> Maths
<input type="checkbox" name="physics" value="on"> Physics
</form>
</body>
</html>
```

This will produce the following result:

☐ Maths ☐ Physics

## Attributes

Following is the list of attributes for <checkbox> tag.

Attribute	Description
type	Indicates the type of input control and for checkbox input control it will be set to checkbox.
name	Used to give a name to the control which is sent to the server to be recognized and get the value.
value	The value that will be used if the checkbox is selected.
checked	Set to <i>checked</i> if you want to select it by default.

## Radio Button Control

Radio buttons are used when out of many options, just one option is required to be selected. They are also created using HTML <input> tag but type attribute is set to radio.

Example

Here is example HTML code for a form with two radio buttons:

```
<!DOCTYPE html>
<html>
<head>
<title>Radio Box Control</title>
</head>
<body>
<form>
<input type="radio" name="subject" value="maths"> Maths
```

```
<input type="radio" name="subject" value="physics"> Physics
```

```
</form>
```

```
</body>
```

```
</html>
```

This will produce the following result:

☐ Maths ☒ Physics

### Attributes

Following is the list of attributes for radio button.

Attribute	Description
type	Indicates the type of input control and for checkbox input control it will be set to radio.
name	Used to give a name to the control which is sent to the server to be recognized and get the value.
value	The value that will be used if the radio box is selected.
checked	Set to <i>checked</i> if you want to select it by default.

### Select Box Control

A select box, also called drop down box which provides option to list down various options in the form of drop down list, from where a user can select one or more options.

#### Example

Here is example HTML code for a form with one drop down box

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>Select Box Control</title>

</head>

<body>

<form>

<select name="dropdown">

<option value="Maths" selected>Maths</option>

<option value="Physics">Physics</option>


</select>

</form>

</body>

</html>
```

This will produce the following result:



## Attributes

Following is the list of important attributes of <select> tag:

Attribute	Description
name	Used to give a name to the control which is sent to the server to be recognized and get the value.
size	This can be used to present a scrolling list box.
multiple	If set to "multiple" then allows a user to select multiple items from the menu.

Following is the list of important attributes of <option> tag:

Attribute	Description
value	The value that will be used if an option in the select box box is selected.

selected	Specifies that this option should be the initially selected value when the page loads.
label	An alternative way of labeling options

## File Upload Box

If you want to allow a user to upload a file to your web site, you will need to use a file upload box, also known as a file select box. This is also created using the `<input>` element but type attribute is set to **file**.

### Example

Here is example HTML code for a form with one file upload box:

```
<!DOCTYPE html>
<html>
<head>
<title>File Upload Box</title>
</head>
<body>
<form>
<input type="file" name="fileupload" accept="image/*" />
</form>
</body>
</html>
```

This will produce the following result:

### Attributes

Following is the list of important attributes of file upload box:

Attribute	Description
name	Used to give a name to the control which is sent to the server to be recognized and get



	the value.
--	------------

accept	Specifies the types of files that the server accepts.
--------	---

## Button Controls

There are various ways in HTML to create clickable buttons. You can also create a clickable button using `<input>` tag by setting its type attribute to **button**. The type attribute can take the following values:

Type	Description
submit	This creates a button that automatically submits a form.
reset	This creates a button that automatically resets form controls to their initial values.
button	This creates a button that is used to trigger a client-side script when the user clicks that button.
image	This creates a clickable button but we can use an image as background of the button.

## Example

Here is example HTML code for a form with three types of buttons:

```
<!DOCTYPE html>
<html>
<head>
<title>File Upload Box</title>
</head>
<body>
```

```
<form>
<input type="submit" name="submit" value="Submit" />
<input type="reset" name="reset" value="Reset" />
<input type="button" name="ok" value="OK" />
<input type="image" name="imagebutton" src="/html/images/logo.png" />
</form>
</body>
</html>
```

This will produce the following result:



## Hidden Form Controls

Hidden form controls are used to hide data inside the page which later on can be pushed to the server. This control hides inside the code and does not appear on the actual page. For example, following hidden form is being used to keep current page number. When a user will click next page then the value of hidden control will be sent to the web server and there it will decide which page will be displayed next based on the passed current page.

Example

Here is example HTML code to show the usage of hidden control:

```
<!DOCTYPE html>
<html>
<head>
<title>File Upload Box</title>
</head>
```

```
<body>
<form>
<p>This is page 10</p>
<input type="hidden" name="pagename" value="10" />
<input type="submit" name="submit" value="Submit" />
<input type="reset" name="reset" value="Reset" />
</form>
</body>
</html>
```

This will produce the following result:

Top of Form

This is page 10



## Style Web Forms Using CSS

A big part of our work as website designers is the ability to make things look good and function well. We spend hours taking the time to make every aspect of our site visually compelling, intuitive, user friendly, accessible and overall beautiful. Our forms are no exception! Our forms should be beautiful, easy to use, and should look consistent with the rest of our website. We can do this easily with CSS.

The process isn't difficult, you just can to know what each tag does, and how to style it. The first thing we need to do is bring in our HTML. Below is the HTML found in our sample form.

```
<form>
<div>
  <h1>Contact Form :</h1>
  <label>
```

```
<span>Your name</span><input id="name" type="text" name="name" />

</label>

<label>

  <span>Email Address</span><input id="email" type="text" name="email" />

</label>

<label>

  <span>Subject</span><input id="subject" type="text" name="subject" />

</label>

<label>

  <span>Message</span><textarea id="feedback" name="feedback"></textarea>

  <input type="button" value="Submit Form" />

</label>

</div>

</form>
```

You will notice that in the HTML, I used words, names, and ids that make sense. They are consistent with what you'd expect each field to be called. Each Field is wrapped in a label tag to make things easy for us to style. Our form looks pretty plain without any styling, as you can see from the sample below:



KARPAGAM  
ACADEMY OF HIGHER EDUCATION  
(Deemed to be University)  
(Established Under Section 3 of UGC Act, 1956)

# KARPAGAM ACADEMY OF HIGHER EDUCATION

CLASS: II BSC CS

COURSE NAME: HTML PROGRAMMING

COURSE CODE: 17CSU404A

UNIT: V (FORMS)

BATCH-2017-2020

## Contact Form :

Your name:  Email Address:  Subject:  Message:

Our form has no structure, no color, and no personality. We can change that with a little bit of code. First, we are going to style the form tag itself.

```
form {  
  
    background: -webkit-linear-gradient(bottom, #CCCCCC, #EEEEEE 175px);  
    background: -moz-linear-gradient(bottom, #CCCCCC, #EEEEEE 175px);  
    background: linear-gradient(bottom, #CCCCCC, #EEEEEE 175px);  
  
    margin: auto;  
  
    position: relative;  
  
    width: 550px;  
  
    height: 450px;  
  
    font-family: Tahoma, Geneva, sans-serif;  
  
    font-size: 14px;  
  
    font-style: italic;  
  
    line-height: 24px;  
  
    font-weight: bold;  
  
    color: #09C;
```

```
text-decoration: none;

border-radius: 10px;

padding: 10px;

border: 1px solid #999;

border: inset 1px solid #333;

-webkit-box-shadow: 0px 0px 8px rgba(0, 0, 0, 0.3);

-moz-box-shadow: 0px 0px 8px rgba(0, 0, 0, 0.3);

box-shadow: 0px 0px 8px rgba(0, 0, 0, 0.3);


}
```

The code above can look like a mouthful, but it is fairly simple when broken down. Flat colors can be really boring, so adding a slight gradient can break up the monotony and give your design some dimension. That is done with the background style. When using this property and gradients, you have to include the specific prefixes for certain browsers such as Firefox, or they won't show up. Both are saying the same thing. Create a linear gradient, start from the bottom, and use a medium gray and a light gray and blend it over 175px.

Since this is where your entire form is going to be contained, I decided to center the form in the browser by setting margin to auto. Setting the Position to Relative is intended for aligning an element later, so that explanation is to come. I specified the width and the height of the form, the fonts used, and styled it to be bold, italic, 14px in size and a line height (spacing between each line of text) of 24px.

Border radius gives us rounded corners for our boxes. Increase the number for more rounded corners. Padding gives some space between the text and the edge of the form, so that your text doesn't run outside the bounds of your form and its rounded corners.

You can create subtle borders for contrast and dimension. I also added box shadows to the overall form, so if this becomes a popup form, it will add dimension and make the form look like it is floating over the rest of the site. This is a popular technique right now. This is yet another style that needs you to specify the proper prefix in order to get it to show up. Your form should look something like this:



**Contact Form :**

Your name  Email Address  Subject


Message

Next, we should style the input area. That is where the text is actually entered into each field.

```
input {  
    width: 375px;  
    display: block;  
    border: 1px solid #999;  
    height: 25px;  
    -webkit-box-shadow: 0px 0px 8px rgba(0, 0, 0, 0.3);  
    -moz-box-shadow: 0px 0px 8px rgba(0, 0, 0, 0.3);  
    box-shadow: 0px 0px 8px rgba(0, 0, 0, 0.3);}
```

The code shown above selects all of the text input areas, and styles them to be 375px wide, and setting the display to block stacks them vertically. Adding a 1px border helps to emphasize each input area, and setting the height to 25px gives the user plenty of room visually to enter their text.

I added a box shadow for dimension, but remember to include the prefix for each browser. The first 2 digits control the offset for the shadow. Positive numbers push the shadow to the right and up, and negative numbers push it to the left and down. The 3rd number determines how much the shadow is blurred. The higher the number, the larger the blur. Inside of the parenthesis, the 1st three numbers determine the red, green, and blue values of the shadow, and the decimal number determines the opacity of the shadow itself. 1 is 100% opacity and 0.1 is 10% opacity. With these style added, your form should begin to take shape, and look like the image below:



Everything is aligned, but notice that the submit button has been affected by the width styling. We will fix this later. The message area doesn't look right, but we can fix this easily.





```
textarea#feedback {  
  
    width: 375px;  
  
    height: 150px;  
  
}
```

You can specify the width and the height directly, but this still doesn't make the textarea fall in line with the other fields.

**Contact Form :**

*Your name*

*Email Address*


*Subject*

*Message*

Submit Form

We have to set the `display` property to `block` manually, so that it performs the same way as the input areas.

```
textarea#feedback {  
  
    width: 375px;  
  
    height: 150px;  
  
    display: block;  
  
}
```



**Contact Form :**

**Your name**

**Email Address**

**Subject**

**Message**

Submit Form

Now that everything is aligned properly, we can get down to fixing the submit button.  
The CSS that we need to fix this is fairly simple:

```
button {  
    width: 100px;  
    position: absolute;  
    right: 20px;  
    bottom: 20px;  
    background: #09C;  
    color: #fff;  
    font-family: Tahoma, Geneva, sans-serif;  
    height: 30px;  
    border-radius: 15px;  
    border: 1px solid #999;
```

```
}  
  
input.button:hover {  
  
    background: #fff;  
  
    color: #09C;  
  
}
```

We select the button named submit and define its width to 100px and set its position to absolute. As we mentioned earlier, we had styled the form to have a relative position. The way this works is that when you set something to have a absolute position, it looks for the last element that has its position set to relative. If that element is nested inside of the element with a position of relative, its absolute position is relative to that element. In other words, the submit button will be positioned somewhere inside of the bounds of the form container. I defined that it will be 20px from the right and from the bottom with those respective styles.

I set the background to blue and the text to white. I gave it a definite height of 30px and rounded corners. I also have it a 1px gray border. This is the normal state for your submit button.

You will notice that I defined a hover state for the submit button. The styles defined here override the original styling once the user hovers over the button. I changed the background to white and the text to blue, giving the user a highly contrasting effect when they mouse over the button.

Here is the normal state:

**Contact Form :**

**Your name**

**Email Address**

**Subject**

**Message**

Submit Form

Here is the hover state:

**Contact Form :**

**Your name**

**Email Address**

**Subject**

**Message**

Submit Form

Our form's structure is done. You could stop here and you would have a great form, all styled with CSS. However, you could take it one step further, by adding a little user friendly styling to the text input areas, so that the user can tell where they are typing. You can do this with a small amount of CSS:

```
textarea:focus, input:focus {
```



```
border: 1px solid #09C;
```

```
}
```

What this does is it tells the browser that if a person has a text input or text area selected, that it needs to add a 1px blue border around the active input area, so the user knows where they are visually in the form. This is just a little extra something that is much appreciated by many users.

**Contact Form :**


**Your name**

**Email Address**

**Subject**

**Message**

Submit Form



**Possible Questions**

**Unit-V**

**Part –A**  
(Online Questions)

(1 mark)

**Part –B**

(2 Marks)

1. Define CSS.
2. What is CGI?
3. What are the values of method attribute?
4. What is a form?
5. Write the CSS syntax.
6. Define Text box.
7. What is option button?
8. What is check box?
9. Explain reset button.
10. How submit button is used in html form.

**Part –C**

(6 Marks)

1. What are the other kinds of input in forms?
2. Display an advertisement with the CSS styling in it.
3. Explain about basic input and attributes of forms.
4. Expand and illuminate different tasks in CSS?
5. Describe the 5 main tags used in creating HTML form.
6. Display an advertisement with the CSS styling in it.
7. Discuss about different form controls in detail.
8. Write a program to create a form using HTML which has the following types of controls:
  - I. Text Box
  - II. Option/radio buttons
  - III. Check boxes
  - IV. Reset and Submit buttons
9. Explain about styling forms with CSS.

Register Number: \_\_\_\_\_  
[17CSU404A]

**KARPAGAM ACADEMY OF HIGHER EDUCATION**  
**Coimbatore-641021.**  
**B.Sc COMPUTER SCIENCE**  
**FIRST INTERNAL EXAMINATION - DECEMBER 2018**  
**Fourth Semester**  
**HTML PROGRAMMING**

**Class: II B.Sc. CS**  
**Date & Session: 19 .12.2018**

**Duration : 2 Hours**  
**Maximum : 50**

---

**PART-A (20 X 1 = 20 Marks)**  
**Answer ALL the Questions**

1. What does HTML stand for?  
a.Home Tool Markup Language                      b.Hyper Text Markup Language  
c.Hyperlinks and Text Markup Language        d.Hyper Tool Mark language
2. Choose the correct HTML tag for the largest heading  
a.<h6>      b.<h5>              c.<h1>      d.<h3>
3. Select the HTML tag for inserting a line break?  
a.<br />      b.<lb>              c.<break>      d.<brk>
4. What is the HTML tag for adding a background color?  
a.<body color="yellow">                      b. <background>yellow</background>  
c.<body bgcolor="yellow">                      d. <body=yellow color>
5. What tag is used to make a text bold  
a.<bld>              b.<bb>              c.<b>              d.<bold>
6. Choose the HTML tag to make a text italic  
a.<ii>              b.<italics>              c. <i>              d.<it>
7. How can you make a list that lists the items with numbers.  
a.<ul>              b.<ol>              c.<dl>              d.<list>
8. How can you make a list that lists the items with bullets?  
a.<list>              b.<ol>              c.<ul>              d.<dl>
9. \_\_\_\_\_ is the tag used to define the paragraph  
a.p              b. pa              c.paragraph              d.para

10. \_\_\_\_\_ is the tag used to define horizontal line  
a.hr      b.hrr      c.br      d.brr
11. HTML file is saved with extension \_\_\_\_\_  
a .ht      b..html      c. .txt      d. .doc
12. \_\_\_\_\_ defines the smallest heading.  
a.<h6>      b. <h1>      c. <h3>      d. <h2>
13. \_\_\_\_\_ Defines the document's body  
a.<body>      b.<bg>      c.<bodyDoc>      d.<body statement>
14. \_\_\_\_\_ element is used to designate a section of text that is already formatted for display.  
a.<body>      b.<background>      c.<pre>      d.<dis>
15. \_\_\_\_\_ element is used to denote italics  
a.<i>      b. <tt>      c. <u>      d.<it>
16. \_\_\_\_\_ is used for underline  
a.<i>      b.<tt>      c.<u>      d.<ul>
17. \_\_\_\_\_ element showing subscripts.  
a.<sup>      b. <sub>      c.<s>      d. <super>
18. \_\_\_\_\_ element showing superscripts.  
a.<sup>      b.<sub>      c. <s>      d.<super>
19. HTML definition is given in the file as  
a.Last line      b. First line      c. Not given      d. Optional
20. Colors can be given to fonts using \_\_\_\_\_ attribute  
a.bgcolor      b.clr      c. color      d.backgroundColor

### **PART-B**

**(3 X 2 = 6 Marks)**

**Answer ALL the Questions**

21. What is HTML?
22. List out the different types of lists used in Html.
23. What is href? Give Example.



**PART-C** **[3 \* 8 = 24 Marks]**  
**Answer ALL of the following.**

24. a) What is metadata? List out the different types of tags used in html.

(OR)

b) Explain in detail about <body> tag with neat examples.

25. a) What is Color tag? List out hexacode values used in the Html ?

(OR)

b) Describe in detail about attributes tags used in html with Example.

26. a) Explain in detail about the different types of lists with suitable example.

(OR)

b) Discuss in detail about the relative links with neat examples.

Reg No \_\_\_\_\_

[17CSU404A]

**KARPAGAM ACADEMY OF HIGHER EDUCATION**

(Deemed to be University)

(Established Under Section 3 of UGC Act 1956)

**Fourth Semester**

(For the candidates admitted from 2017 onwards)

**SECOND INTERNAL EXAMINATION, FEBRUARY 2019**

**Computer Science/Information Technology/Computer Technology**

**HTML PROGRAMMING**

**Class :II B.Sc CS**

**Maximum Marks : 50**

**Date :5.02.19-AN**

**Time: 2 Hours**

**PART-A**

**[20 \* 1 = 20Marks]**

**Answer all of the following**

1. Which of the following tag is used to link the URL?  
a. <a>                      b. <style>                      c. <link>                      d. <hyperlink>
2. Link URL in HTML is specified using \_\_\_\_\_ attribute.  
a. src                      b. href                      c. link                      d. rel
3. A tag stands for \_\_\_\_\_  
a. anchor tag                      b. active tag                      c. action tag                      d. additional tag
4. Value of attribute "href" is also called as \_\_\_\_\_ of the destination web page  
a. URS                      b. URK                      c. URM                      d. URL
5. The \_\_\_\_\_ attribute is used to define an "alternate text" for an image.  
a. alt                      b. align                      c. Src                      d. alter
6. \_\_\_\_\_ tag is used to define an image.  
a. <img>                      b. <image>                      c. <im>                      d. <img picture>
7. \_\_\_\_\_ tag is used to define a clickable area inside an image map.  
a. <imgmap>                      b. <area>                      c. <image>                      d. <img>
8. The \_\_\_\_\_ attribute specifies a background-image for an HTML page.  
a. background                      b. Bground                      c. backimg                      d. bgimg
9. Visited Link in Mozilla firefox is generally shown in \_\_\_\_\_ color.  
a. brown                      b. purple                      c. blue                      d. red

10. Default color of active link in browser is\_\_\_\_\_.
- a. brown      b. purple      c. blue      d. Red
11. What attributes are used to specify the dimension of an image?
- a. height      b. width      c. both height and width      d. size
12. What tag was used to display the picture?
- a. picture      b. image      c. img      d. src
13. Relationship between the current document and the linked document is specified using \_\_\_\_\_ attribute
- a. rel      b. relation      c. target      d. href
14. Which of the following is not a valid alignment attribute?
- a. Left      b. Right      c. Top      d. All of above
15. Which attribute is used with img tag to display the text if image could not load in browser?
- a. description      b. name      c. alt      d. id
16. Which of the following is used to open document in new window?
- a. <a target=“\_self”>Link</a>      b. <a target=“\_blank”>Link</a>  
c. <a target=“\_top”>Link</a>      d. <a target=“\_parent”>Link</a>
17. \_\_\_\_\_attribute is used to specify MIME type of linked document
- a. rev attribute      b. type attribute      c. source attribute      d. srs attribute
18. \_\_\_\_\_ attribute is used to display an image.
- a. src attribute      b. val attribute      c. source attribute      d. srs attribute
19. Which are the special tags used for image mapping?
- a. map and area      b. map and usemap      c. Only map      d. Only usemap
20. Which element follows the use of “img”\_\_\_\_\_.
- a. area      b. usemap      c. map      d. Any element

## **PART-B**

**[3 \* 2 = 6 Marks]**

### **Answer all of the following**

21. What is target attribute?
22. Define <img> tag.
23. What is src attribute?

**PART-C**

**[3 \* 8 = 24 Marks]**

**Answer all of the following**

24. a) Explain about ID attribute to link within a document.

**OR**

b) Explain about how to use styling links in a web page.

25.a)Elaborate in detail about server side image map with an example.

**OR**

b) Illustrate about the <table> with their relevant attributes.

26. a)List out any five types of attributes used in the <img> tag and explain it.

**OR**

b) Create a table using HTML which consists of columns for Roll No., Student's name and grade

Reg No \_\_\_\_\_

[16CSU404A]

**KARPAGAM ACADEMY OF HIGHER EDUCATION**

(Deemed to be University)

(Established Under Section 3 of UGC Act 1956)

**Fourth Semester**

**THIRD INTERNAL EXAMINATION, MARCH 2018**

**COMPUTER SCIENCE**

**HTML PROGRAMMING**

**Class :II B.Sc CS**

**Maximum Marks : 50**

**Date : 12.03.18**

**Time : 2 Hours**

**PART-A**

**[20 \* 1 = 20Marks]**

**Answer all of the following**

1. \_\_\_\_\_ using to create a separate table footer.

a.<table>                      b.<thead>                      c.<tbody>                      d.<tfoot>

2. A table may be contain a several \_\_\_\_\_ element to indicate different pages or Groups of data.

a.<table>                      b.<thead>                      c.<tbody>                      d.<tfoot>

3. An HTML table contain a set of \_\_\_\_\_

a.rows and columns    b.tags                      c.cells                      d.attributes

4. Each rows consist of one or more \_\_\_\_\_

a.rows                      b.columns                      c.cells                      d.tags

5. Table can be divided into \_\_\_\_\_ portions.

a.two.    b.one.    c.seven    d.three

6. What are the three main parts of a table?.

a.rows,columns,cells.    b.header,body,footer.    c.columns,rows,cells.    d.footer,header,body

7. \_\_\_\_\_ using to create a separate table header.

a.<thead>                      b.<th>                      c.<td>.                      d.<tr>

8. \_\_\_\_\_ using to indicate the main body of the table.

a.<table>                      b.<thead>                      c.<tbody>                      d.<tfoot>

9. Radio buttons have \_\_\_\_\_  
a. square boxes   b. lines   c. rectangle boxes   d. rounded hollow buttons
10. \_\_\_\_\_ are form elements that provides user to select one of the option  
a. textbox   b. checkbox   c. radio button   d. button
11. Which tag creates a check box for a form in HTML?  
a. <checkbox>   b. <input type="checkbox">   c. <input=checkbox>   d. <input checkbox>
12. Which among the following is not a form control?  
a. Text boxes   b. Password fields   c. Check boxes   d. Scroll bar
13. A \_\_\_\_\_ is a set of one or more rules that apply to an HTML document  
a. tables   b. frames   c. Stylesheet   d. forms
14. Large text can be given in forms using  
a. text   b. large   c. largertext   d. textarea
15. To avoid users from changing the size of browser window \_\_\_\_\_ tag is used  
a. resize   b. noresize   c. nochange   d. change
16. A website can be made interactive with the help of \_\_\_\_\_  
a. tables   b. frames   c. Text   d. forms
17. There are \_\_\_\_\_ main parts in a form  
a. 1   b. 2   c. 3   d. 4
18. \_\_\_\_\_ tag is used initially to create a form  
a. <FORM>   b. <CREATE>   c. <INITIAL>   d. <CREATEFORM>
19. \_\_\_\_\_ method is used to submit user information to the server  
a. GET   b. SUBMIT   c. POST   d. RESET
20. \_\_\_\_\_ are used to select different kinds of user input.  
a. HTML Forms   b. HTML Table   c. Html Lists   d. HTML frames

## **PART-B**

**[3 \* 2 = 6 Marks]**

**Answer all of the following**

21. Write the syntax for creating the table.
22. What is <thead>tag?
23. What is a form?

**PART-C**

**[3 \* 8 = 24 Marks]**

**Answer all of the following**

24. a) What are all the tags used in creating a table?

**OR**

b) Explain in detail about spanning multiple columns.

25. a) Explain about creating a table header with a program.

**OR**

b) Discuss about different form controls in detail.

26. a) Explain about basic input and attributes of forms.

**OR**

b) Explain about styling forms with CSS.

Reg. No.....

[11NMU401E]

**KARPAGAM UNIVERSITY**

(Under Section 3 of UGC Act 1956)

COIMBATORE - 641 021

(For the candidates admitted from 2011 onwards)

**B.Sc., DEGREE EXAMINATION, APRIL 2013**

Fourth Semester

**COMPUTER SCIENCE**

**WEB DESIGNING USING HTML**

Time: 3 hours

Maximum : 100 marks

**PART - A (15 x 2 = 30 Marks)**

**Answer ALL the Questions**

1. What is HTML and abbreviate it.
2. Explain the properties used with body tag.
3. Describe the ordered list tag and the unordered list tag.
4. Write about the tags used for predefined text.
5. Explain subscript and superscript tags with example.
6. What are the properties used to set the image size?
7. How to change the color of the cell in the table?
8. What is the tag used to create the table? Is it a singular tag or paired tag?
9. Write about heading across 2 or more columns.
10. How to create check boxes?
11. Write about resetting the form.
12. What is a frame? Which tag is used for it?
13. Abbreviate DHTML and CSS
14. How to create changeable box.
15. Write about the font family in CSS.

**PART B (5 X 14= 70 Marks)**

**Answer ALL the Questions**

16. (a) Discuss
  - i. HTML? ii. The history of HTML. iii. Basic structure of a HTML Program

Or

- (b) Explain the tags used to format the text in HTML Program.

17. (a) Write the Tags to create alphabetical list and roman numbered list. Also the tags for square unordered list

Or

- (b) Create links to display related images in the new page.

18. (a) Create a table for displaying student's personal detail.

Or

- (b) Display a table of 5 rows and 5 columns. Each cell should have unique color in the background.

19. (a) Create forms with menus, check boxes and radio buttons. Using reset button reset the values of the form to default.

Or

- (b) Create forms with menus, check boxes and radio buttons. Also with submit and reset buttons.

20. (a) Explain moving boxes and the Changeable boxes.

Or

- (b) Write about the font family in CSS and demonstrate it.



Reg. No.....

[11NMU401E]

## KARPAGAM UNIVERSITY

(Under Section 3 of UGC Act 1956)

COIMBATORE - 641 021

(For the candidates admitted from 2011 onwards)

### B.Sc., DEGREE EXAMINATION, NOVEMBER 2013

Fourth Semester

COMPUTER SCIENCE

WEB DESIGNING USING HTML

Time: 3 hours

Maximum : 100 marks

#### PART - A (15 x 2 = 30 Marks)

Answer ALL the Questions

1. Explain font tag with its properties
2. Which tag is used to include image in web page and explain
3. Explain : i. Singular Tag ii. Paired tag
4. Write about the tag used for preformatted text.
5. Describe about the unordered list tag with its properties.
6. Write about `<a> --</a>` tag.
7. What are the inner tags for creating table?
8. How to give a heading for two columns?
9. Which property is used in which tag for aligning the content of the cell?
10. What is a form? Which tag is used to create a form?
11. How to create text box in a form?
12. What is a password box? How to create a password box?
13. What is a hidden message?
14. Create a basic style sheet.
15. Write about the horizontal line in DHTML.

#### PART B (5 X 14= 70 Marks)

Answer ALL the Questions

16. (a) Discuss the evolution of the HTML. Write a basic structure of the HTML program.  
Or  
(b) Write a HTML program with the following properties:  
i. Style ii. Size iii. Bold tag, italic tag, underlined tag  
iv. Superscript tag, subscript tag, strike through tag

17. (a) Discuss about predefined font, preformatted font, definition list, ordered list,  
Or

- (b) Write a HTML program to display an alphabetical list of numbers and a numbered list of alphabets with minimum of 5 members in each.

18. (a) Create a table to enter the product details with required fields.

Or

- (b) Create a table which has the links to the new page whereas the new page has the table of student details.

19. (a) Create forms with menus, check boxes and radio buttons. Using reset button reset the values of the form to default.

Or

- (b) Create forms with menus, text boxes and text areas. Also with submit and reset buttons.

20. (a) Write about the Horizontal line, moving boxes and changing boxes.  
Demonstrate it.

Or

- (b) Write about the CSS, its working principles, colours and font family.

Reg. No.....

[12CSU503]

**KARPAGAM UNIVERSITY**

(Under Section 3 of UGC Act 1956)

COIMBATORE - 641 021

(For the candidates admitted from 2012 onwards)

**B.Sc., DEGREE EXAMINATION, NOVEMBER 2014**

Fifth Semester

**COMPUTER SCIENCE**

**PROGRAMMING WITH HTML AND JAVASCRIPT**

Time: 3 hours

Maximum : 100 marks

**PART - A (15 x 2 = 30 Marks)**

**Answer ALL the Questions**

1. Write short notes on history of HTML.
2. Give out the syntax for a simple HTML program.
3. Write down the syntax and example for creating hyper links in HTML.
4. Write short notes on creating a Table (syntax and example).
5. How will you create header cells in a HTML table?
6. Give out the attributes for
  - i. Adding a border around a table.
  - ii. Changing background color of a table.
7. Write down the tag suitable for dividing a web page into segments.
8. Define DHTML and mention its features.
9. What is the process for creating moving boxes?
10. Delineate events in JavaScript.
11. Define Java Script?
12. What is meant by operators in JavaScript?
13. What is an Object?
14. Mention any two event handlers.
15. List out any two color properties.

**PART B (5 X 14 = 70 Marks)**

**Answer ALL the Questions**

16. (a) Develop a HTML page to display an advertisement and give a link to another page.

Or

- (b) i) Explain about XML and HTML.

ii) Create a paragraph in HTML document and give different font type for each line.

17. (a) i. List out all internet browsers known and explain any three.  
ii. Explain the operations for resetting a form with example.

Or

- (b) Explicate the basic form controls in HTML with an example.

18. (a) Illustrate Hidden Message, Moving Boxes and Changeable Box with an example.

Or

- (b) Discuss in detail about Font Family in CSS.

19. (a) What is meant by an Event, Explain with Example?

Or

- (b) Illustrate Variables, Data types and Statements with example.

**20. Compulsory :-**

Create a web page for an On-line Examination with HTML and JavaScript.





Reg. No.....

[11NMU401E]

**KARPAGAM UNIVERSITY**

(Under Section 3 of UGC Act 1956)

COIMBATORE – 641 021

(For the candidates admitted from 2011 onwards)

**B.Sc., DEGREE EXAMINATION, NOVEMBER 2014**

Fourth Semester

**COMPUTER SCIENCE**

**WEB DESIGNING USING HTML**

Time: 3 hours

Maximum : 100 marks

**PART – A (15 x 2 = 30 Marks)**

**Answer ALL the Questions**

1. Which tag is used for  
i. Superscript    ii. Subscript    iii. Strike through
2. Explain the properties of font tag.
3. What is the abbreviation of :    i. HTML    ii. CSS
4. Write about the tag for block quote
5. Which tag is used to create link between two pages?
6. What is predefined font?
7. How to divide a table into rows using tags?
8. How to add a background image in a table?
9. What are the properties of a table tag?
10. What is a menu? How to create menu?
11. How to create password boxes?
12. Write about resetting form.
13. Create a moving box using DHTML.
14. What are the common tasks done with CSS?
15. Explain definition list with the tag.

**PART B (5 X 14= 70 Marks)**

**Answer ALL the Questions**

16. a. Define HTML. What is the history of HTML?  
Or  
b. What are the tags used to format the text. Explain.

17. a. Write a HTML Program to create the following list: with examples  
i. Ordered list    ii. Unordered list    iii. Definition list

Or

b. Define :

- i. Predefined font    ii. Blocking quote
- iii. Blinking text    iv. Preformatted text

Write a HTML program to demonstrate the above tags

18. a. Create a table with 5 rows and 5 columns with background image and border.  
Or  
b. Create a table with a heading for 3 columns and each row with different colors, and different content alignment.
19. a. Create forms with menus, check boxes and radio buttons.  
Or  
b. Create a form to get the user's personal details with submit and reset button.
20. a. Explain DHTML and its features.  
Or  
b. Discuss about CSS and its working features.

**KARPAGAM UNIVERSITY**

(Under Section 3 of UGC Act 1956)

COIMBATORE - 641 021

(For the candidates admitted from 2012 onwards)

**B.Sc., DEGREE EXAMINATION, JANUARY 2015**

Fifth Semester

**COMPUTER SCIENCE****PROGRAMMING WITH HTML AND JAVASCRIPT**

Time: 3 hours

Maximum : 100 marks

**PART - A (15 x 2 = 30 Marks)****Answer ALL the Questions**

1. Define HTML.
2. List out the attributes in font tag.
3. How to create superscript and subscript text in your document?
4. What is the attribute used to change the color of specific cell in a table?
5. How can you span more than one column in a table?
6. Write down the attribute for aligning cell contents in a table.
7. How to create changeable boxes in DHTML?
8. Define CSS.
9. Write short notes on linking style sheets into a HTML document.
10. Make clear about the comparison operator.
11. What is the use of assignment statement and give out an example?
12. What function is used to create an alert in a web page?
13. Define Object.
14. Mention the classification of objects.
15. Delineate "Browser Objects".

**PART B (5 X 14= 70 Marks)****Answer ALL the Questions**

16. a. Enlighten about Lists in HTML, with examples.  
Or  
b. i. Create a paragraph in HTML page, use superscript and subscript in it.  
ii. Create a web page with image size as 250 X 300 and create a hyper link to next page

17. a. Explain in detail with example :

- i. Putting background image into a table.
- ii. Heading across two or more columns in a table.
- iii. Creating borders in table.

Or

- b. Discuss about the process of aligning content and changing color of the cell in a table and how would you divide the table in various columns?

18. a. Write the HTML coding for the following table structure and apply formatting with content.


Or

- b. Explicate about heading and horizontal line and hidden message in DHTML.

19. a. Develop a webpage to display a hotel menu of items using Java Script.

Or

- b. Explain: i. Alert using Java Script with an example  
ii. The working of Assignment Statement.

**20. Compulsory :-**

Illustrate String Objects with example.

